

Express Mail No. EL844351855US

**PATENT APPLICATION OF**

**Barry Wendt, Benidict Wittig, Mira K.  
LaCous and Gary L. Zarn**

**ENTITLED**

**IMAGE IDENTIFICATION SYSTEM**

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205

## **IMAGE IDENTIFICATION SYSTEM**

### BACKGROUND OF THE INVENTION

The present invention relates generally to image identification systems. More specifically, the present invention relates to methods and procedures for improving the performance and reliability of image identification systems.

Image identification systems have been used in the past, one application being biometric image identification systems. One type of biometric image identification system is a fingerprint identification system. In a fingerprint identification system, a user places the tip of a finger on a scanning surface of a fingerprint image reader device. Each ridge of the epidermis (outer skin) is dotted with sweat glands that produce moisture that, in combination with oily secretions and other substances naturally present on the tip of a finger, enable an image of a fingerprint to be scanned. (The present invention can also be successfully applied to images generated from readers that do not rely on the moisture content of the skin to capture an image.). The fingerprint image reader device creates an image scan by capturing a picture of fingerprint ridge characteristics present on the tip of a finger. In many systems, the image is then compared to a database of other stored fingerprint images or fingerprint image models for verification, authentication, or some other form of analysis.

Security systems that implement fingerprint identification technology have the potential of being reliable and easy to use. These benefits arise from the fact that the technology does not require a system user to retain any piece of knowledge, such as a password, personal identification number, combination or any other code. Neither must a user possess a card, key or any other physical device to gain access to a secured environment. A fingerprint security authentication key, as opposed to a knowledge or possession based security authentication key is nearly impossible to lose, steal, or be forgotten.

Development of practical security system applications that incorporate fingerprint image identification technology has been hindered by a general non-repeatability of data from one image scan to another. In particular, physical variations present in the environment of a fingerprint reader device can cause substantial incongruities from one image scan of a fingerprint as compared to a subsequently taken image scan of the same fingerprint. Differences in the temperature, amount of pressure applied to the scanning surface, moisture content of the finger, as well as the effects of medications and differences in blood pressure can all contribute to substantial incongruities from one image scan to another. These incongruous results hinder the development of most fingerprint identification technology applications because inconsistent data

leads to an unacceptably high number of false acceptances (multiple identifications, which include matching to wrong people) and false rejections (not recognizing an enrolled user) for applications that  
5 might require instantaneous and unsupervised comparisons to be made between a scanned fingerprint image and a database of fingerprint images or fingerprint models. Another problem associated with many image identification systems is the small  
10 amount of data gleaned by the typical system from each image. For instance, most fingerprint identification systems are minutiae-based, typically meaning that only rods, islands, and bifurcations are cataloged and made available for analysis. An ideal image scan  
15 performed by a minutiae-based system will typically glean a maximum of approximately 50 useful data points, and this count may be further compromised by data points that might not appear in the scanned image due to previously discussed interference in the image  
20 reader environment. The discrimination capability of the typical minutiae-based identification system is not adequate for applications that require instantaneous and accurate comparisons to be made between a real-time scanned image and a database of  
25 potential matching images or models. In addition, systems that glean only a small number of useful data points are more susceptible to fraudulently produced fingerprint forgeries.

Yet another problem associated with the average image identification system is that they prove to be an inefficient model for making comparisons between a real-time scanned image and a database of potential matching images or models. Most systems compare the real-time scanned image or model derived from that scan with each of the images or models contained within a database of images or models on a one-to-one basis until a matching pair is located. Depending on the size of the database, the time required to locate a matching pair can be substantial.

Due to these classical limitations on image identification technology, image identification applications have typically been limited to use in low security and/or supervised environments within which quick processing is not a priority. For instance, many law enforcement agencies that currently utilize fingerprint identification systems operate within the confines of minutiae-based matching. A minutiae-based system may be adequate in such an environment where a fingerprint expert may be available to take the time necessary to supervise the system and act as the arbiter in cases of multiple matches to an online database.

Minutiae-based systems, and other traditional fingerprint identification systems, are not adequate for unsupervised mass market applications, such as an automatic teller machine (ATM) that incorporates a fingerprint identification system and requires the

user to submit a valid fingerprint scan when using an ATM card to make a money transaction. Neither are traditional systems appropriate for authentication systems designed to selectively and instantaneously  
5 provide access to places and devices such as computers, computer networks, facilities, automobiles and appliances based on the receipt of an authorized image. Efficient and effective functionality of these types of applications depend on a level of rapid and  
10 accurate analysis that cannot be consistently achieved by the traditional fingerprint image identification system.

Another benefit associated with an authentication system that incorporates image identification is that  
15 such a system is tunable, meaning the discrimination level or the match requirements during image comparison can be adjusted based on the nature of the environment to be secured and the desired level of security associated therewith. Due to burdens of non-  
20 repeatability of data, false match acceptances, and false match rejections, the range and number of levels within which a traditional image identification system can be tuned is narrowly limited. Such a system may not be tunable at all. Even the highest level of  
25 discrimination in a traditional system provides a substantially limited amount of discrimination.

SUMMARY OF THE INVENTION

Methods and procedures for improving the performance and reliability of image analysis within  
5 an image identification system include a series of image qualification functions designed to quickly process a fraction of available scanned image data and to provide feedback to a system user pertaining to image quality and authenticity. In one embodiment, if  
10 image qualification leads to the conclusion that the scanned image is fraudulent or of insufficient quality, then processing of the image is interrupted.

Also included in the present invention are functions designed to produce image models based on  
15 original image data and to catalogue such image models into a searchable database. In accordance with one embodiment, the creation of an image model involves analyzing and manipulating image data received from an image reader, and new data sets originating therefrom.  
20 Image models enrolled within a searchable database, in accordance with one embodiment of the present invention, can be derived either from a single scan of an object or from two or more scans of the same object.

25 The present invention also includes functions for comparing one image model to another. In accordance with one embodiment, a series of shift and rotate algorithms are applied to at least one of the image models until a position at which the two models best

compare is identified. A score that represents a relationship or percentage of data elements that are common between the two image models is computed. In accordance with one embodiment, the level of similarity required in order for two image models to be considered matching is tunable.

Finally, the present invention provides functions for making a quick determination as to which, if any, of a potential thousands (or more, i.e., millions to hundreds of millions) of image models within a searchable database exhibit a desired level of similarity, as compared to a target image model. In accordance with one embodiment, rather than comparing image models specifically, a set of database index keys that describe different image model characteristics are defined and enable general, rather than specific comparisons to be made. In accordance with one embodiment, discrimination levels can be tuned.

20

#### BRIEF DESCRIPTION OF THE DRAWINGS

The file of this patent contains at least one drawing executed in color. Copies of this patent with color drawings will be provided by the Patent and Trademark Office upon request and payment of the necessary fee.

FIG. 1 is a block diagram of a fingerprint imaging system.



FIG. 2 is a flow diagram illustrating operations to be carried out within the fingerprint imaging system according to the present invention.

FIG. 3 is a pictorial representation of an example set of image scan parameters.

FIG. 4 is a block diagram illustrating a set of procedural components corresponding to an image qualification portion of the operations shown in FIG. 2.

FIG. 5 is an illustration of a raw scan image.

FIG. 6 is an illustration of an intermediate image produced in accordance with a preprocessing portion of the operations shown in FIG. 4.

FIG. 7 is an illustration of a monochrome image produced in accordance with the preprocessing portion of the operations shown in FIG. 4.

FIG. 8A is an illustration of a monochrome image derived from a Mylar film source using an LED light source within an image reader.

FIG. 8B is an illustration of a monochrome image derived from a paper source using an LED light source within an image reader.

FIG. 8C is an illustration of a monochrome image derived from a live finger source using an LED light source within an image reader.

FIG. 9A is an illustration of a monochrome image derived from a Mylar film source using an infrared light source within an image reader.

FIG. 9B is an illustration of a monochrome image derived from a paper source using an infrared light source within an image reader.

FIG. 9C is an illustration of a monochrome image  
5 derived from a live finger source using an infrared light source within an image reader.

FIG. 10 is an illustration of a monochrome image after a contour trace has been completed in accordance with a slope table generation portion of the  
10 operations shown in FIG. 4.

FIG. 11 is an illustration of a monochrome image with a slope overlay based on a slope table completed in accordance with the slope table generation portion of the operations shown in FIG. 4.

FIG. 12 is an illustration of a histogram  
15 completed in accordance with a histogram generation portion of the operations shown in FIG. 4.

FIG. 13 is an illustration of the histogram  
20 overlaying a raw scan image from which the histogram was derived.

FIG. 14 is an illustration of a histogram cell.

FIG. 15 is a block diagram illustrating a set of procedural components corresponding to a model creation portion of the operations shown in FIG. 2.

FIG. 16 is a block diagram illustrating a set of  
25 procedural components corresponding to a preprocessing portion of the operations shown in FIG. 15.

FIG. 17 is an illustration of a corrected raw scan image.

FIG. 18 is an illustration of an intermediate image produced in accordance with a preprocessing portion of the operations shown in FIG. 15.

FIG. 19 is an illustration of an enhanced image.

5        FIG. 20 is an illustration of a monochrome image produced in accordance with a preprocessing portion of the operations shown in FIG. 15.

10       FIG. 21 is an illustration of a monochrome image after irregularities in the image have been located and filled.

FIG. 22 is an illustration of a filled monochrome image.

FIG. 23 is an illustration of a smoothed and filled monochrome image.

15       FIG. 24 is a pictorial representation of an alternate set of example image scan parameters.

20       FIG. 25 is an illustration of a monochrome image after a contour trace has been completed in accordance with a slope table generation portion of the operations shown in FIG. 15.

FIG. 26 is an illustration of a monochrome image with a slope overlay based on a slope table completed in accordance with the slope table generation portion of the operations shown in FIG. 15.

25       FIG. 27 is a block diagram illustrating a set of procedural components corresponding to a wire-frame generation portion of the operations shown in FIG. 15.

FIG. 28 is an illustration of a monochrome image after a first removal of pixels from image ridge lines.

FIG. 29 is an illustration of a monochrome image with a comprehensive representation of pixel removal passes made during the thinning of the monochrome image to the center-most ridge line pixels.

FIG. 30 is an illustration of FIG. 29 further including an overlay of a thinned monochrome image having raw wire-frame lines.

FIG. 31 is an illustration of a thinned monochrome image with raw wire-frame lines.

FIG. 32 is an illustration of a thinned monochrome image after excess pixels have been removed from the raw wire-frame lines.

FIG. 33 is an illustration of the relationship between a thinned monochrome image, after excess pixels have been removed, and a corresponding monochrome image.

FIG. 34 is an illustration of a thinned monochrome image, with excess pixels removed, that includes a representation of data from an end-point table.

FIG. 35 is an illustration of a thinned monochrome image, with excess pixels removed, that includes a representation of data from a center-point table.

FIG. 36 is an illustration of a refined set of wire-frame lines.

FIG. 37 is an illustration demonstrating the relationship between the refined set of wire-frame lines and a corresponding monochrome image.

FIG. 38 is an illustration demonstrating the relationship between a further refined set of wire-frame lines, including fixed end-points, and a corresponding monochrome image.

FIG. 39 is an illustration demonstrating the relationship between the further refined set of wire-frame lines, including fixed and joined end-points, and a corresponding monochrome image.

FIG. 40 is a graphical representation of a fingerprint bifurcation image element.

FIG. 41 is a graphical representation of a fingerprint rod image element.

FIG. 42 is an illustration of a wire-frame fingerprint image within which qualified bifurcations and rods have been circled.

FIG. 43 is an illustration of the wire-frame fingerprint image within which qualified bifurcations and rods have been circled and vector segments have been traced.

FIG. 44 is a block diagram illustrating a set of procedural components associated with a one-to-one image comparison process.

FIG. 45 is a block diagram illustrating a set of procedural components associated with a one-to-many database image comparison process.

FIG. 46 is a block diagram illustrating a set of procedural components associated with another one-to-many database image comparison process.

5        DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

10        The present invention relates to methods and procedures for improving the performance and reliability of image identification systems generally. The inventive concepts could be applied within systems designed to operate in conjunction with a broad range of image types, including but not limited to license plate images, graphic images and text based images. In addition, the present invention provides methods and procedures that are particularly suitable for  
15        improving the performance and reliability of fingerprint image identification systems specifically. While the remainder of the detailed description will discuss the present invention in relation to fingerprint image identification systems, it is to be  
20        understood that the concepts of the present invention could just as easily be applied within other types of image identification systems.

25        FIG. 1 is a block diagram of a fingerprint imaging system 10 within which the methods and procedures of the present invention could be applied. Imaging system 10 includes a reader portion 12, image analyzer/processor 14 and searchable database 16, which further includes an output 15. Reader portion 12 could be any of a number of known systems capable

of scanning an image of a fingerprint and transferring data pertaining to the image to an image analyzer, such as image analyzer/processor 14.

In many cases, reader portion 12 will include an optical device that includes a reflecting face designed to receive the finger to be imaged. Light is input into the optical device by a light emitter and an optical image of the finger is reflected out of the optical device to an imager which receives the image and produces an analog image signal indicative of the optical signal received. In many systems, the analog signal is then transferred to a conventional analog/digital converter, which produces a digital representation of the analog signal. The digital signal is reformatted into a digitized image which can be stored and, in accordance with an embodiment of the present invention, manipulated. Finally, the digitized image is transferred out of the reader portion to an image analyzer/processor 14. Image analyzer/processor 14 varies with application, but generally analyzes the image data received for a wide variety of purposes and applications.

In an embodiment of the present invention, as will be discussed in more detail below, image analyzer/processor 14 creates an image model based on the particular features and characteristics of each image received from reader portion 12. These image models are more than facsimiles of their associated fingerprint images and include a unique range of data

elements that provide analytical opportunities that are a part of the present invention.

In one embodiment of the present invention, image analyzer/processor 14 compares data elements of one  
5 image model to data elements of at least one other image model stored within searchable database 16. The image models contained in database 16 correspond to previously obtained scanned images, while the image model being compared typically corresponds to a  
10 contemporaneously scanned image. Fingerprint imaging system 10, through the incorporation of this process, is able to quickly and efficiently make a determination as to whether the image model corresponding to the contemporaneously scanned  
15 fingerprint is substantially similar to any of the image models included within the searchable database 16. As will be discussed more fully below, system 10 requires a particular level of similarity for a match to be indicated. In accordance with one embodiment,  
20 the level of required similarity is adjustable and can be tuned based on the nature of the environment for which system 10 is designed to provide security. In this manner, fingerprint imaging system 10 provides an efficient and accurate fingerprint image  
25 identification system that can be used, for instance, as a security measure to determine whether the person who places a finger on the reader portion 12 should be authorized to enter a room, to access a bank account or to take any other variety of actions.



As is shown in FIG. 1, searchable database 16 includes an output 15. The precise nature of output 15 depends on the context within which imaging system 10 is to be applied. For instance, output 15 could be an identification indicator of an image contained in searchable database 16 that substantially matches the image scanned by reader portion 12. This is but one example of the many potential forms of output 15.

FIG. 2 is a flow diagram illustrating operations to be carried out within system 10, specifically within analyzer/processor 14, in accordance with an embodiment of the present invention. The process begins when image analyzer/processor 14 receives image data from reader portion 12. After receiving image data, image analyzer/processor 14 first performs, as is indicated by block 18 in FIG. 2, a series of image qualification functions.

Details pertaining to image qualification 18 will be discussed in greater detail with respect to FIG. 4. Briefly, image qualification 18 involves quickly processing a fraction of the available image data to ensure that the received image is a scan of a real fingerprint (as opposed to a fraudulent fingerprint) and of sufficient quality to proceed with processing. In one embodiment, if the image qualification process leads to the conclusion that the scanned image is fraudulent or of insufficient quality, then processing of the image is stopped or interrupted. In such a case, the system user is provided with feedback

pertaining to identified inadequacies and is allowed to continue processing only when the inadequacies have been corrected. Only a fraction of available image data is processed during image qualification 18 in order to expedite processing and to enable feedback to be provided to a system user on a substantially real time basis.

Once the image has been qualified, the next step, as is indicated by block 20 in FIG. 2, is the creation of an image model. Model creation 20 will be described in greater detail with respect to FIG. 15. Briefly, model creation 20 involves analyzing and manipulating image data received from reader portion 12, and new data sets originating therefrom, until an image model is produced. Due to an increased need for accuracy, the image data processed during model creation 20 is a complete set of image data, as opposed to the fractional set processed during image qualification 18. While the procedure for creating and the composition of an image model will be described in greater detail below, it should be emphasized that an image model is a collection of data based on the original print image and is not a facsimile of the original print image.

After an image model has been created, in accordance with an embodiment of the present invention, the image model is utilized for one of two purposes. First, as is indicated in FIG. 2, is model enrollment 22. Model enrollment 22 is the process

with which image models are entered into and catalogued within searchable database 16. Image models enrolled within database 16, in accordance with one embodiment of the present invention, can be  
5 derived either from a single scan of a fingerprint image or from two or more scans of the same fingerprint image. When two or more scans are used to create an image model, consistent model elements that show up from scan to scan are noted in the image  
10 model. Inconsistent model elements, for example, discrepancies in the image data that are the result of previously mentioned variations in the reader environment, are eliminated.

In one embodiment of the present invention, when  
15 two or more scans are being utilized during model enrollment 22, the finger is removed from the reader portion 12 after each scan and then is subsequently replaced before the next scan is taken. In accordance with another embodiment, a significant amount of time  
20 may pass between scans. Because environmental factors such as finger pressure, finger moisture and finger positioning can vary from scan to scan, removing the finger from reader portion 12 between scans increases the likelihood that environmental inconsistencies will  
25 be eliminated when they do not show up in each individual scan.

As is indicated by block 24 in FIG. 2, and in accordance with another embodiment of the present invention, the other purpose for which an image model

can be utilized is model comparison 24. Model comparison 24 will be described in greater detail below. Briefly, model comparison 24 is a process that can be utilized to compare one image model to another.

5 Model comparison 24 is accomplished by applying a series of shift and rotate algorithms to at least one of the image models until a position at which the two models best compare is identified. Then, a score that represents a relationship or percentage of data

10 elements that are common between the two image models is computed.

As is indicated by block 26 in FIG. 2, and in accordance with an illustrative embodiment of the present invention, database search 26 could be

15 performed in place of or in combination with model comparison 24. Database search 26 will be described in greater detail below. Briefly, database search 26 involves a quick and efficient determination as to which, if any, of a potential thousands, or even

20 millions, of image models within database 16 exhibit a desired level of similarity, as compared to a target image model. In accordance with one embodiment, the target image model is an image model associated with a contemporaneously scanned image. Rather than

25 comparing image models specifically, a set of database keys that describe different image model characteristics are defined and enable general, rather than specific comparisons to be made during the database search 26 process. The desired level of

similarity is adjustable and could be selected based on a desired processing speed, a desired level of security, and other characteristics indicative of the environment for which system 10 is designed to provide security.

It should be emphasized that nearly all, with an anti-spoofing procedure to be discussed later in this application being a primary exception, of the methods and procedures of the present invention are not dependent upon the inclusion of a particular reader portion 12 and can be retrofitted to work with any reader technology. For the purpose of illustrating embodiments of the present invention, however, an example set of image scan parameters that correspond to an example reader portion 12 will be adopted. In particular, the example parameters will correspond to a SACcat™ fingerprint reader device offered and marketed by Secured Access Control Technologies (doing business as BIO-key International), of Eagan, Minnesota.

FIG. 3 is a pictorial representation of details pertaining to the example set of image scan parameters. The example parameters are generally indicated by reference numeral 28 and are not critical to the present invention. The example reader portion 12, which produces the example parameters 28, illustratively includes a camera that has an aspect ratio of 4 to 3 and provides 64 levels of gray-scale, where neither value is critical to the present

invention. As is illustrated by FIG. 3, image scan parameters 28 include a scan area 30 which is larger than a processing area 32. Processing area 32 is part of scan area 30 and is the only portion of scan area 30 that provides data that is actually captured for analysis. Within scan area 30, there are 510 lines and 488 pixels per line. For the purpose of simplifying explanation of the present invention, it is to be assumed that the reader portion 12 produces no linear distortion due to optics (a flat image is assumed).

FIG. 4 is a block diagram illustrating a set of procedural components corresponding to the image qualification 18 portion of the operations illustrated in FIG. 2. It should be emphasized that the primary purpose of image qualification 18 is to ensure that the image data received by image analyzer/processor 14 from reader portion 12 is a scan of a non-fraudulent fingerprint and of suitable quality for subsequent image processing.

In accordance with an embodiment of the present invention, as was previously alluded to, all of the functions within image qualification 18 are carried out utilizing a fraction of the image data potentially available for analysis. In one embodiment, analyzer/processor 14 receives a complete set of image data from reader portion 12 but utilizes only every other line and every other pixel of information for analysis during image qualification 18. In other

words, only one quarter of the data within processing area 32 is analyzed during image qualification 18. The purpose of processing only a fraction of available data is to expedite processing, thereby enabling  
5 feedback pertaining to image quality and authenticity to be provided to a system user in a substantially real time manner. Upon receiving real time feedback, a system user is then allowed to adjust variables (change pressure applied to scanning surface, produce  
10 a non-fraudulent image source, wipe excessive moisture from finger, etc.) until all negative feedback is remedied and the image scan is of sufficient quality to continue with the processing of the image.

In more detail, image qualification 18 begins  
15 with preprocessing 34 (see FIG. 4). When analyzer/processor 14 receives image data from reader portion 12, it is in a raw scan, also known as gray-scale, format. The general purpose of preprocessing 34 is to reduce data. More particularly, the purpose  
20 is to convert the raw scan image into a monochrome image or binary image, which is desirable for subsequent image qualification 18 processing. In accordance with one embodiment, preprocessing 34 is utilized to convert the raw scan image into an image  
25 that incorporates single bits that are black or white.

During preprocessing 34, a raw scan image, similar to raw scan image 46 in FIG. 5, is received from reader portion 12 and first transformed into an intermediate image similar to intermediate image 48 in

FIG. 6. As the Figures illustrate, intermediate image 48 is similar to raw scan image 46 but includes enhancements of primary features. To accomplish the image transformation, in accordance with an embodiment of the present invention, each pixel in intermediate image 48 is created by averaging an  $n \times n$  pixel (where  $n$  is greater than 1) array taken from the raw scan image 46. In accordance with one embodiment,  $3 \times 3$  pixel arrays are utilized. The pixel (new pixel value) at row  $y$  and column  $x$  in intermediate image 48 is given by:

Equation 1

```
    Set new pixel value to zero.
15   For  $x_1$  values of  $x-1$  to  $x+1$  do
      For  $y_1$  values of  $y-1$  to  $y+1$  do
        Add to new pixel value the value of the pixel in
        Raw Scan at  $x_1$  and  $y_1$ 
        Divide new pixel value by 9.
20  Store new pixel value in an intermediate image buffer
    at row  $y$  and column  $x$ .
```

The next step in preprocessing 34, in accordance with one embodiment, is to convert intermediate image 48 (FIG. 6) into a monochrome image similar to monochrome image 50 in FIG. 7. In accordance with an embodiment of the present invention, the transformation from intermediate image 48 (FIG. 6) to monochrome image 50 (FIG. 7) is accomplished as follows: Each pixel in the monochrome image is created by comparing the  $5 \times 5$  average value of a pixel taken from intermediate image 48 with a  $3 \times 3$



average for the same pixel location. It should be pointed out that different sizes of pixel arrays could be utilized without departing from the scope of the present invention. The pixel (new pixel value) at row  
5 y and column x in the monochrome image is given by:

Equation 2.

Set average\_1 value to zero.  
For x1 values of x-2 to x+2 do  
10 For y1 values of y-2 to y+2 do  
Add to average\_1 value the value of the pixel in  
enhanced image at x1 and y1  
Divide average\_1 value by 25 (5 multiplied by  
5).  
15 Set average\_2 value to zero.  
For x1 values of x-1 to x+1 do  
For y1 values of y-1 to y+1 do  
Add to average\_2 value the value of the pixel in  
enhanced image at x1 and y1  
20 Divide average\_2 value by 9 (3 multiplied by 3).  
If average\_2 value is greater than average\_1 value  
Then set pixel value to zero  
Else, set pixel value to 255.  
Store pixel value in monochrome image at row y and  
25 column x.

With reference to FIG. 4, another process incorporated within image qualification 18 is anti-spoofing 36. In order for fingerprint imaging system  
30 10 to incorporate anti-spoofing techniques as described herein, a reader portion 12 that includes both an infrared light source and an LED light source for shining light into an optical device must be incorporated in the system. Of course, with other  
35 readers, other anti-spoofing technologies can be

implemented. Anti-spoofing 36 is a method for detecting a non-live finger, such as a fake finger, a drawing on paper or a photo-plot on Mylar film. Anti-spoofing also provides protection against the  
5 prerecorded/playback of live scans. Anti-spoofing, in accordance with one embodiment of the present invention, involves the capture and comparison of two consecutive images, where the first image is side-lit by an infra-red light source and the second image is  
10 back-lit by a visible LED light source.

The anti-spoofing process starts by insuring that the back-lit LED light source is turned off. Next, the side-lit infra-red light source is turned on. In accordance with one embodiment, this switching of  
15 light sources is performed on a random basis to defeat prerecorded/playback spoofing attack scenarios. The infra-red lit image is captured and, in one embodiment, is preprocessed in accordance with previously described preprocessing 34 to produce a  
20 first monochrome image. Monochrome images 58, 59, and 60, respectively depicted in FIGS. 9A, 9B and 9C, illustrate images derived using an infra-red light source to scan images contained on a Mylar film source, a paper source and a live finger source, also  
25 respectively.

The next step in the anti-spoofing process is to turn off the infra-red light source and to turn on the back-lit LED light source in order to capture a second image, which in accordance with one embodiment, is

preprocessed and transformed into a second monochrome image. Monochrome images 52, 54, and 56, respectively depicted in FIGS. 8A, 8B and 8C, illustrate images derived using a back-lit LED light source to scan  
5 images from a Mylar film source, a paper source and a live finger source, also respectively.

In the final step of anti-spoofing, the infra-red originated monochrome images are compared to the LED originated monochrome images and matching pixel values  
10 are noted. Generally, live finger image scans will produce a very high correlation of like values as compared to images based on fraudulent image sources. Illustratively, images 56 and 62 are substantially the same, whereas the primary features in images 52 and  
15 58, and images 54 and 60 include pixels having values substantially opposite to one another (i.e. a feature that is black in one image is not black in the corresponding comparison image). In one embodiment of the present invention, fingerprint imaging system 10,  
20 when confronted with results that indicate a non-live image has been presented, will terminate further processing until a live finger is presented for scanning.

It should be noted that while the anti-spoofing  
25 method has been described in relation to the comparison of monochrome scan images, the anti-spoofing process could just as easily be applied to raw scan or other image configurations. Because monochrome images, however, are comprised of a limited

range of pixel values, they provide a smooth comparative model that typically produces a clear and accurate result.

Referring to FIG. 4, another component within the image qualification 18 process is slope table generation 38. The purpose of the slope table, once it is generated, is not to create information directly used to provide feedback to the system user, but to create a statistical tool that is used as an aid in subsequent image qualification 18 processing. Specifically, the slope table could be used to supplement histogram generation 40 and could be used during print center determination 42.

To begin slope table generation 38, the monochrome image created during preprocessing 34, illustratively monochrome image 50 (FIG. 7), is first divided into an array of  $n \times n$  pixel grids (where  $n$  is greater than 1). In one embodiment, an array of  $8 \times 8$  pixel grids is utilized. In accordance with this embodiment, and in accordance with example image scan parameters 28 (FIG. 3), an array of  $8 \times 8$  pixel grids yields 27 grids in the  $x$  direction and 29 grids in the  $y$  direction.

To aid in the creation of the slope table, a raw slope table is first created. The raw slope data table is illustratively, in accordance with example parameters 28, a two dimensional array  $27 \times 29$  where each entry in the table contains three entries:

1. A count of the changes in the  $x$  coordinate.

2. A count of the changes in the y coordinate.
3. A count of the pixels tested.

The raw slope data table is created by doing a contour trace of the features within each pixel grid of the array of pixel grids into which monochrome image 50 has been divided. As the trace migrates through the pixel grids, the three elements included in the raw slope data table are incremented. Below is a diagram showing the values to be added to the raw slope data table for the eight possible next pixel combinations (P is the current pixel, N is the next pixel, \* represents an ordinary pixel and serves as a filler for display purposes):

Equation 3

***	***	***	***
*PN	*P*	*P*	*P*
***	**N	*N*	N**
x = + 1 y = 0	x = + 1 y = + 1	x = 0 y = + 1	x = - 1 y = + 1
***	N**	*N*	**N
NP*	*P*	*P*	*P*
***	***	***	***
x = - 1 y = 0	x = - 1 y = - 1	x = 0 y = - 1	x = + 1 y = - 1

Image 64 in FIG. 10 is an illustration of a monochrome image after the contour trace has been completed.

When the contour trace has been completed throughout every pixel grid and the raw slope data table is complete, the slope table is ready to be generated. The slope table is a two-dimensional array and, in accordance with example parameters 28 (FIG. 3), is 27 x 29. Each entry in the slope table consists of a single entry, namely the slope of a ridge or ridges flowing through each particular pixel grid. Initially, all entries in the slope table are set to a -one (invalid slope). The slope for each pixel grid is calculated utilizing information from the raw slope data table and is specifically computed as follows:

Equation 4

```
Set x coordinate count to zero.
Set y coordinate count to zero.
Set pixel count value to zero.
For x1 values of x-1 to x+1 do
  For y1 values of y-1 to y+1 do
    from raw slope table at coordinates x1 and y1 do
      Add to pixel count the count of pixels tested.
      Add to x coordinate count the changes in the x
        coordinate.
      Add to y coordinate count the changes in the y
        coordinate.
    from raw slope table at coordinates x and y do
      Add to pixel count the count of pixels tested then
        divide by 2.
      Add to x coordinate count the changes in the x
        coordinate then divide by 2.
      Add to y coordinate count the changes in the y
        coordinate then divide by 2.
      If the pixel count is greater than 10
      Then compute the slope using the trig function
        arcsine.
```

Find angle function

5       Input: delta y and delta x (computed previously  
      above)

      Set quadrant to 0

      If delta y is less than 0

          Then add 2 to quadrant

10       If delta x is less than 0

          Then add 1 to quadrant

      Hypotenuse = square root of ((delta x times  
      delta x) + (delta y times delta y))

15       Angle = arcsine (delta y divided by hypotenuse)  
      times degrees per radian.

      If quadrant is 1

          Then angle = 180-angle

      Else if quadrant is 2

          Then angle = 360-angle

20       Else if quadrant is 3

          Then angle = 180+angle

      Since slopes have values between 0 and 180, the  
      angle is converted to a slope as follows:

25       If angle is equal to or greater than 180

          Then slope is angle minus 180

          Else slope is the angle

      Increment number of pixels processed by one.

30

      Image 66 in FIG. 11 is an illustration of a  
      monochrome image with a slope overlay based on a  
      completed slope table.

35       Referring to FIG. 4, another component of image  
      qualification 18 is histogram generation 40. A  
      completed histogram is used within imaging system 10  
      to determine the quality of scanned fingerprint image  
      data and the adequacy of the image data for subsequent  
      processing.

A completed histogram is a multiple dimensioned  $n \times n$  array (where  $n$  is greater than 1), illustratively two dimensional, and in accordance with example parameters 28 (FIG. 3), a  $6 \times 6$  array. Each cell within the array corresponds to a portion of the image data under analysis. Image 68 in FIG. 12 is an illustration of a completed histogram that includes cell 67, in addition to other unlabeled cells. Image 70 in FIG. 13 is an illustration of the same completed histogram overlaying the raw scan image from which the histogram was illustratively derived. Assigning different portions of an image to different cells of the histogram array enables multiple individual quality determinations to be made for limited quantities of image data corresponding to each of the different histogram cells, rather than a single quality determination being made for the entire set of image data. In one embodiment of the present invention, these multiple quality determinations can be utilized to selectively exclude portions of the image data corresponding to cells that demonstrate low quality characteristics. After low quality cells have been excluded, a positive or negative system determination can be made as to whether enough data cells of acceptable quality are available for subsequent processing.

In accordance with an embodiment of the present invention, each cell of a histogram includes a histogram list. The histogram list, in accordance



with the above described example reader portion 12, is an array of 64 entries (zero to 63). Each entry is assigned a pixel value (example reader portion 12 has 64 potential pixel values) and includes a count of the number of image data pixels having the assigned pixel value. Each histogram cell also illustratively includes a count of the number of pixels within the cell that are processed and classified in the histogram list.

It is to be understood that some reader technologies may require histograms with different configurations in order for accurate quality determinations to be made. For instance, some reader portion 12 technologies may include a broader or narrower range of pixel values. It is to be understood that histograms tailored to accommodate other reader portion 12 technologies are still within the scope of the present invention.

A more detailed description of the functions performed during the generation of an illustrative two dimensional, 6 x 6 histogram array during the histogram generation 40 portion of image qualification 18 is as follows:

Equation 5

Box width is defined as the number of pixels per line divided by 6 (every other pixel included).  
Box height is defined as the number of lines divided by 6 (every other line included).  
For x values of zero to line length do  
For y values of zero to number of lines do

Pixel value is contents of raw scan image  
at coordinates x and y.

Slope table x coordinate is at x divided by  
8 (illustrative slope table grid size).

5        Slope table y coordinate is at y divided by  
8 (illustrative slope table grid size).

      If the contents of the slope table is not -  
1

10                (Recall -1 represents an area that the  
slope could not be computed).

      Then

15                Histogram table x coordinate is at x  
divided by Box width.

      Histogram table y coordinate is at y  
divided by Box height.

Increment histogram list, at index pixel value, by  
one.

20

      In one embodiment of histogram generation 40,  
image quality is divided into four classifications:

1.    Excellent.
2.    Good.
- 25    3.    Fair.
4.    Poor.

25

In addition, those areas that are considered to have  
fair or poor quality may have two additional  
attributes: too dark or too light.

30        The precise details as to the types of data  
elements recorded in a completed histogram, and how  
those data elements are interpreted to make image  
quality classifications differ depending on the type  
of data desired and the reader portion 12 that is  
35        being used within fingerprint imaging system 10. In

other words, quality classification can be tuned in accordance with the type of image quality data desired and in accordance with a particular reader portion 12.

In one embodiment of quality classification, the data recorded in each histogram cell includes seven particular data elements. In the interest of simplifying description, the seven data elements shall be given labels A-G. Histogram cell 72 in FIG. 14 includes data elements A-G, which illustratively correspond to the following information:

Equation 6

- 15 A. Represents the number of pixels in the histogram list corresponding to the most white 25% of the listed pixel values.
- B. Represents the number of pixels in the histogram list corresponding to the most white 35% of the listed pixel values.
- 20 C. Maximum height between points B and F. (not used in quality determination)
- D. Average pixel value. (not used in quality determination)
- E. Minimum height between points B and F. (not used in quality determination)
- 25 F. Represents the number of pixels in the histogram list corresponding to the most black 35% of the listed pixel values.
- G. Represents the number of pixels in the histogram list corresponding to the most black 25% of the listed pixel values.
- 30

In accordance with one embodiment of quality determination, image data quality is determined by comparing the columns associated with points A, B, F and G. Specifically, image data quality is illustratively determined as follows:

Equation 7

5	Excellent:	A - B	$\leq 2$	and
		B	$> 59$	and
		F - G	$\leq 2$	and
		F	$< 5$	
10	Good:	A - B	$\leq 2$	and
		B	$> 55$	and
		F - G	$\leq 2$	and
		F	$< 9$	
15	Fair light:	B	$> 59$	and
		F	$> 10$	
	Fair dark:	B	$< 59$	and
		G	$< 10$	
	Poor light:	B	$> 59$	and
		F	$> 30$	
	Poor dark:	B	$< 59$	and
		G	$< 30$	
20				

As will be discussed in more detail below, feedback relating to the ascertained image quality is provided to a system user in accordance with feedback interaction 44.

Referring again to FIG. 4, print center determination 42 is another component that could be included within image qualification 18. Print center determination 42 is performed by analyzing image data in order to find the center of the associated print image. One way that print center determination 42 could be accomplished is through the application of a set of filter rules to data contained in the slope table generated during slope table generation 38. After the print center has been determined, a further determination is made as to whether a new scan should

be taken with the system user's finger repositioned on an imaging surface of reader portion 12. Feedback relating to this further determination is provided to a system user in accordance with feedback interaction 44.

Referring once again to FIG. 4, feedback interaction 44 is another potential component of image qualification 18. As was previously mentioned, reader portion 12 of fingerprint imaging 10 (FIG. 1) is capable of capturing a live scan of a fingerprint. In accordance with feedback interaction 44, as image analyzer/processor 14 receives fingerprint image data from reader portion 12 and performs the functions of image qualification 18 on a fraction of that data, substantially real time feedback and instructions are provided to the user of system 10 as to inadequate characteristics of the scanned image data that might be improved. Feedback and instructions for the correction of inadequacies of image data might pertain to the proper positioning of the user's finger on reader portion 12 (print center determination 42). Alternatively, they may pertain to the detection of a live finger (anti-spoofing 36) or to image data quality characteristics (histogram generation 40). In one embodiment of the present invention, feedback pertaining to the moisture content of the system user's finger may also be provided.

Once image qualification 18 has been completed, the next step, as is indicated by block 20 in FIG. 2

is the creation of an image model. FIG. 15 is a block diagram illustrating a set of procedural components that, in accordance with an embodiment of the present invention, make up model creation 20. To enhance the accuracy of model creation 20, substantially all available image data, in one embodiment, all the image data included within example processing area 32 (FIG. 3), is made available to image analyzer/processor 14 for model creation 20 processing. This stands in contrast to the fraction of data processed during image qualification 18 for speed and efficiency purposes. While some of the components of model creation 20 are similar to components of imaging qualification 18, none of the data sets generated during image qualification 18 are utilized during model creation 20. Model creation 20, like image qualification 18, starts with a set of raw scan image data and proceeds from that point.

Model creation 20, in accordance with FIG. 15, begins with anti-spoofing 74. Anti-spoofing 74 is an optional step and is performed in substantially the same manner and for the same reasons described above in relation to anti-spoofing 36, a procedural component of image qualification 18. One key difference between anti-spoofing 74 and anti-spoofing 36, however, is that anti-spoofing 74 is performed utilizing a complete data set, whereas anti-spoofing 36 is performed utilizing only a fraction of available data. The purpose of anti-spoofing 74 is to provide

further insurance that the source of raw scan image data is not a fraudulent one. In accordance with one embodiment of the present invention, when anti-spoofing 74 leads to the indication that the source of raw scan data is fraudulent, then subsequent processing is terminated until a valid image source is submitted to system 10.

Anti-spoofing 74 could be performed utilizing raw scan image data or an alternate image data format produced during model creation 20. For instance, anti-spoofing 74 could be performed utilizing monochrome images that, as will be discussed below, are the product of preprocessing 76. In other words, while anti-spoofing 74 has been illustrated in FIG. 15 as the first step in model creation 20, it could be performed later in the model creation 20 process, or, because anti-spoofing 74 is optional, the step could be eliminated altogether.

An early step in the model creation 20 process, as is indicated by block 76 in FIG. 15, is preprocessing 76. The purpose of preprocessing 76 is to produce a monochrome image with an adjusted aspect ratio and with smooth and distinct features suitable for subsequent processing. Preprocessing 76 is different than the preprocessing step described above in relation to image qualification 18. In particular, preprocessing 76 is performed utilizing a complete, rather than fractional, set of available image data. In addition, preprocessing 76 includes some additional

steps intended to eliminate irregularities and inconsistencies in the resulting monochrome image. These steps, while unnecessary for image qualification 18, prove to be beneficial to subsequent processing 5 during model creation 20 processing.

FIG. 16 is a block diagram illustrating the primary procedural components of preprocessing 76, in accordance with an embodiment of the present invention. As is illustrated by block 90, an early 10 step in the process is to generate a set of image data similar to the raw scan image data but with a modified aspect ratio. In accordance with one embodiment, the aspect ratio is adjusted to a 1 to 1 configuration. The correction of the aspect ratio is necessary for 15 subsequent processing that involves rotation of the image and its corresponding data. Conceivably, model creation 20 could be carried out without adjusting the image aspect ratio, but the adjustment is beneficial to procedures carried out after model creation 20, 20 such as model comparison 24.

In accordance with an embodiment of the present invention, the aspect ratio of a raw scan image is modified by copying the raw scan image line by line and replicating lines at appropriate times and places 25 so as to produce a corrected raw scan image with the desired aspect ratio scale. Image 98 in FIG. 17 is an illustration of a corrected raw scan image, wherein the aspect ratio of a raw scan image has been adjusted to 1 to 1.



Another component of preprocessing 76, in accordance with block 92 in FIG. 16, is the conversion of a corrected raw scan (image 98 in FIG. 16) into a monochrome image. Because a monochrome image produced accordingly will be based on all available image data associated with an image having a modified aspect ratio, it is unlikely that this monochrome image will be identical to the one generated during image qualification 18. In addition, characteristics within the model creation 20 monochrome image, as will be described below, are eventually modified and manipulated to emphasize particular image characteristics. This emphasizing of image characteristics is beneficial to model creation 20 but is unnecessary for image qualification 18.

In accordance with an embodiment of the present invention, the first step in the conversion of a corrected raw scanned image to a monochrome image is the creation of an intermediate image. The purpose of creating an intermediate image is to average features within the corrected raw scan image that are predominantly too light or too dark, possibly due to the moisture content of a system user's finger or lighting characteristics. Averaging of these features creates a resultant image that provides for more complete and consistent wire frame generation which follows in subsequent processing steps. In accordance with one embodiment, to create the intermediate image, each pixel is selected by averaging a 5 x 5 pixel

array taken from a corrected raw scan of an image (corrected meaning that the image aspect ratio has been adjusted). The pixel (new pixel value) at row y in column x in the intermediate image is given by:

5

Equation 8

Set new pixel value to zero.

For x1 values of x-2 to x+2 do

For y1 values of y-2 to y+2 do

10 Add to new pixel value the value of the pixel in Corrected Raw Scan at x1 and y1

Divide new pixel value by 25 and round to the nearest integer value.

15 Store new pixel value in intermediate image at row y and column x.

Image 100 in FIG. 18 is an illustration of an intermediate image. It is to be understood that, without departing from the spirit of the present invention, other sized pixel arrays could be utilized during the transformation to intermediate image format.

In accordance with one embodiment of the transformation from a corrected raw scan image format to a monochrome image format, after an intermediate image has been obtained, an edge detect algorithm is applied to the intermediate image in order to produce an enhanced image. In accordance with one embodiment, the edge detect algorithm is applied as follows:

30

Equation 9

Set new pixel value to six times the value of the pixel in intermediate image at row y and column x.

Subtract from new pixel value the value of the pixel in intermediate image at row y-1 and column x-1.

5 Subtract from new pixel value the value of the pixel in intermediate image at row y-1 and column x+1.

Subtract from new pixel value the value of the pixel in intermediate image at row y+1 and column x-1.

10 Subtract from new pixel value the value of the pixel in intermediate image at row y+1 and column x+1.

If new pixel value is less than zero, set new pixel value to zero.

15 Store new pixel value in enhanced image at row y and column x.

Image 102 in FIG. 19 is an illustration of an enhanced image after the edged detect algorithm has  
20 been applied.

The final step of the block 92 portion of preprocessing 76 (FIG. 16) is to transform the enhanced image into a monochrome image format. In one illustrative embodiment, each pixel in the monochrome  
25 image is created by determining an average pixel value of a large grid area and comparing this average to the average pixel value of a smaller grid area for the same pixel location. A threshold separation variance between the average pixel values of the large and  
30 small pixel grids is utilized for the determination of setting the corresponding pixel at that location to a white or black level (i.e., monochrome image result). Pixel grid sizes and threshold values can be chosen to accommodate the characteristics of the image reader  
35 being utilized. In accordance with one embodiment,

the pixel (new pixel value) at row y in column x in the monochrome image is given by:

Equation 10

```
5  Set average_1 value to zero.
    For x1 values of x-6 to x+6 do
        For y1 values of y-6 to y+6 do
            Add to average_1 value the value of
the pixel in edge detect image at x1 and y1
10  Divide average_1 value by 169 (13 multiplied by
    13).
    Set average_2 value to zero.
        For x1 values of x-1 to x+1 do
            For y1 values of y-1 to y+1 do
15  Add to average_2 value the value of
the pixel in edge detect image at x1 and y1
    Divide average_2 value by 9 (3 multiplied by 3).
    If average_2 value is greater than average_1
value plus 4
20  Then set pixel value to zero
    Else, set pixel value to 255.
    Store pixel value in monochrome image at row y
and column x.

25  Image 104 in FIG. 20 is an illustration of a
monochrome image produced accordingly.

    Another component of preprocessing 76, as is
indicated by block 94 in FIG. 16, is to locate and
fill irregularities, in particular small holes, within
30 the monochrome image. Locating and filling small
holes in the monochrome image is necessary so that a
wire-frame image that is subsequently derived from the
monochrome image during model creation 20 will not
have bubbles or voids in it. The irregularity
35 location process is performed by scanning a monochrome
image, such as image 104 in FIG. 20, until an
```

unprocessed pixel value of zero is detected. At that point, the detected pixel is marked as being processed and a recursive descent routine is called. Each zero value pixel is marked as processed and corresponding x and y coordinates stored in a table. When no further zero value pixels can be located, the size of zero value pixel areas is calculated (number of x and y coordinate entries in the table). Illustratively, if the area size is 35 pixels or less, the 35 pixel value being selected based on the image characteristics outlined in relation to FIG. 3, and provided the shape of the area is roughly a circle, the area is filled using a pixel value of 255. The number of pixels required in order for an area to be considered for filling can be adjusted to accommodate a particular reader portion 12 without departing from the spirit of the present invention. When the entire monochrome image has been checked, the block 94 process is complete.

Image 106 in FIG. 21 is an illustration of a monochrome image, such as image 104 in FIG. 20, after irregularities have been located and, for illustrative purposes, filled with pixels having a substantially white value. In accordance with one embodiment of the present invention, the center coordinates of the white filled areas within image 106 in FIG. 21, and the size of these areas are stored in a table and classified as data element points. These data element points, illustratively called micro-minutia, classified by

their location and associated slope value of the ridge they reside on, are image data points that are unique to a particular system user and, in combination with other data element points, can be catalogued and  
5 utilized in the comparison of one set of image scan data to another. The micro-minutia points are small, (as small as one thousandth of an inch in diameter), and likely represent the locations of a system user's sweat glands. It should be noted that the number of  
10 micro-minutiae points identified in an image scan is substantially dependent upon the resolution capabilities of a particular reader portion 12 and upon the condition of the fingertip (wet, dry, damaged, etc.). The higher the resolution capability  
15 of the reader portion 12, the more micro-minutiae points available for identification.

The final component of preprocessing 76, in accordance with block 96 in FIG. 16, is to smooth and fill image elements within the monochrome image. In  
20 the case of fingerprint image data, the image elements within the monochrome image are typically fingerprint ridge elements. The smooth and fill process is designed to add and remove pixels on the border of fingerprint ridge elements. Smoothing the boundaries  
25 along the ridge elements optimizes the quality of subsequently produced wire-frame images, which are derived from the completed monochrome image later in the model creation 20 process.

The input to the smooth and fill 96 process, in one embodiment, is the monochrome image after it has been filled in accordance with block 94. Image 108 in FIG. 22 is an illustration of a filled monochrome image, wherein filled pixels no longer includes a substantially white value, as was the case in FIG. 21. The output from the smooth and fill 96 process is a smooth monochrome image similar to image 110 in FIG. 23. To make the transformation, each pixel in the filled monochrome image is used as the center of a 3 x 3 array. Each of the surrounding eight pixels are used to form an index into a table. The content of each table entry contains two flags:

1. Do nothing
2. Set the center pixel

Below are the indexes into the table for those values that contain the set flag. All other table entries contain the do nothing flag.

Equation 11

5   6   7	[where the index value is equal to
--- --- ---	the binary sum of pixel locations
4   P   0	that are present and is represented
--- --- ---	as a hexadecimal value (i.e.; pixel
3   2   1	location 4 if present = $2^{4th}$ which
	equals decimal value 16); and where
	Count equals the number of pixels
	present in a 3x3 array surrounding
	the center "P" pixel location.]

25



index value 0x4F: \* \*\*\* \*\* \*

index value 0x1D: FILL - Count = 4

index value 0x74: \*\* \* \*\*

5 index value 0xD1: \*x\* \*x \*x\* x\*

index value 0x47: \*\* \*\* \*

index value 0x7B: FILL - Count = 6

index value 0xED: \* \* \*\* \*\* \*\*\*

10 index value 0xB7: \*x\* x\* \*x\* \*x

index value 0xDE: \*\* \*\*\* \* \* \*\*

index value 0x37: FILL - Count = 5

index value 0xDC: \*\* \*\* \* \*\*

15 index value 0x73: \*x\* \*x \*x\* x\*

index value 0xCD: \* \*\* \*\* \*\*

index value 0x5E: FILL - Count = 5

index value 0x79: \*\*\* \* \* \*\*

20 index value 0xE5: \*x \*x\* x\* \*x\*

index value 0x97: \* \*\* \*\*\* \*

index value 0x16: FILL - Count = 3

index value 0x58: \*\* \* \*

25 index value 0x61: \*x \*x x\* x\*

index value 0x85: \* \*\* \*

index value 0x67: FILL - Count = 5

index value 0x9D: \*\* \*\* \*\* \*

index value 0x76:    x\*    \*x\*    \*x    \*x\*  
 index value 0xD9:    \*\*           \*    \*\*           \*\*

index value 0x6F:    FILL - Count + 6  
 5 index value 0xBD:    \*\*\*    \*\*           \*\*    \*    \*  
 index value 0xF6:    x\*    \*x\*    \*x    \*x\*  
 index value 0xDB:    \*\*    \*    \*    \*\*\*    \*\*

index value 0x17:    FILL - Count = 4  
 10 index value 0x5C:    \*\*    \*\*           \*  
 index value 0x71:    \*x\*    \*x    \*x\*    x\*  
 index value 0xC5:           \*    \*\*    \*\*

index value 0xFF:    FILL - Count = 8  
 15           \*\*\*    \*\*\*    \*\*\*    \*\*\*  
              \*x\*    \*x\*    \*x\*    \*x\*  
              \*\*\*    \*\*\*    \*\*\*    \*\*\*

Referring to FIG. 16, after image smooth and fill  
 20 96 has been completed, preprocessing 76, in accordance  
 with an embodiment of the present invention, is also  
 completed.

Another procedural component of model creation  
 20, in accordance with block 78 in FIG. 15, is slope  
 25 table generation 78. Slope table generation 78 is  
 substantially similar to slope table generation 38  
 described above in relation to FIG. 4 and image  
 qualification 18. The primary difference between  
 slope table generation 78 and slope table generation

38 is that during slope table generation 78, all available image data is processed rather than a fraction of available image data. In addition, slope table generation 78 involves the processing of a unique monochrome image formed in accordance with the procedures of preprocessing 76, rather than the limited monochrome image formed in accordance with the procedures of preprocessing 34.

While slope table generation 38, in accordance with example image scan parameters 28, defined in relation to FIG. 3, involved the processing of an illustrative array of 8 x 8 pixel grids with 27 grids in the x direction and 29 grids in the y direction, slope table generation 78 involves the processing of a more complete data set and a correspondingly different grid configuration. In addition, during model creation 20, example parameters 28 may vary in accordance with aspect ratio adjustments made during preprocessing 76. For example, FIG. 24 is an illustration of an alternate set of example image scan parameters 112 that include a scan area 114 and a processing area 116. Alternate example image scan parameters 112 are similar to example scan parameters 28, but processing area 116 reflects an example change in size configuration that may occur when the aspect ratio of the image scan is adjusted during preprocessing 76.

Therefore, illustratively, in accordance with example image scan parameters 112, slope table

generation 78 is accomplished by dividing the image corresponding to processing area 116 into an illustrative array of 10 x 10 pixel grids. Considering that every pixel and every line is to be  
5 analyzed, this yields 44 grids in the x direction and 60 grids in the y direction. It should be emphasized that the precise values incorporated into the slope table generation process depend on the characteristics of the particular reader portion 12 being utilized.  
10 Analysis can be tailored to accommodate any reader portion 12.

As was explained above in relation to slope table generation 38, there are two tables created during the slope table generation process: the raw slope data  
15 table and the slope table. In accordance with example scan parameters 112, the raw slope data table is a two dimensional array consisting of 44 x 60 cells, where each cell in the raw slope data table consists of three individual entries:

- 20       1. A count of the changes in the x coordinate.  
         2. A count of the changes in the y coordinate.  
         3. A count of the pixels tested.

The raw slope data table is created by doing a contour trace of the monochrome image produced during preprocessing 76. As the trace migrates through the  
25 pixel grids, the three elements included in the raw slope data table are incremented. Below is a diagram showing the values to be added for the eight next pixel combinations (P is the current pixel, N is the

next pixel, \* represents an ordinary pixel and is a filler for display purposes):

Equation 12

5	***	***	***	***
	*PN	*P*	*P*	*P*
	***	**N	*N*	N**
	x=+1	x=+1	x=0	x=-1
	y+ 0	y=+1	y=+1	y=+1
10	***	N**	*N*	**N
	NP*	*P*	*P*	*P*
	***	***	***	***
	x=-1	x=-1	x=0	x=+1
15	y= 0	y=-1	y=-1	y=-1

Image 118 in FIG. 25 is an illustration of the monochrome image, produced in accordance with preprocessing 76, after a contour trace has been completed. When the entire image has been traced and the raw slope data table has been completed, the slope table is generated. Illustratively, the slope table is also a two-dimensional array, consisting of 44 x 60 cells. Each entry in the slope table consists of a single entry, namely, the slope of the ridge or ridges going through the corresponding grid. Initially, all entries in the slope table are set to a -1 (invalid slope). The slope for each pixel grid is calculated

utilizing information from the raw slope data table  
and is computed as follows:

Equation 13

```
5  Set x coordinate count to zero.
    Set y coordinate count to zero.
    Set pixel count value to zero.
    For x1 values of x-1 to x+1 do
      For y1 values of y-1 to y+1 do
10     from raw slope table at coordinates
    x1 and y1 do
      Add to pixel count the count of
    pixels tested.
      Add to x coordinate count the changes
15     in the x coordinate.
      Add to y coordinate count the changes
    in the y coordinate.
      from raw slope table at coordinates x and y
    do
20     Add to pixel count the count of pixels tested
    then divide by 2.
      Add to x coordinate count the changes in the
    x coordinate then divide by 2.
      Add to y coordinate count the changes in the
25     y coordinate then divide by 2.
      If the pixel count is greater than 20
      Then compute the slope using the trig
    function arcsine.

30  Find angle function
    Input: delta y and delta x (computed previously
    above)

    Set quadrant to 0
35  If delta y is less than 0
      Then add 2 to quadrant
    If delta x is less than 0
      Then add 1 to quadrant
    Hypotenuse = square root of ((delta x times
40    delta x) + (delta y times delta y))
```

```
Angle = arcsine (delta y divided by hypotenuse)
      times degrees per radian.
If quadrant is 1
  Then angle = 180-angle
5  Else if quadrant is 2
    Then angle = 360-angle
  Else if quadrant is 3
    Then angle = 180+angle

10  Since slopes have values between 0 and 180, the
    angle is converted to a slope as follows:

    If angle is equal to or greater than 180
      Then slope is angle minus 180
15  Else slope is the angle
Increment number of pixels processed by one.
```

Image 120 in FIG. 26 is an illustration of a monochrome image produced in accordance with preprocessing 76 and with a slope overlay consistent with a completed slope table. The completed slope table is used in subsequent processing. Specifically, it is used as an aid during wire-frame generation 82 in the extension of wire-frame lines and in the removal of unwanted wire-frame lines.

In accordance with block 80 in FIG. 15, and in accordance with an embodiment of the present invention, a histogram could be generated during model creation 20. A histogram resulting from histogram generation 80 could be utilized to make a determination as to image quality within different portions of the image data under analysis. If a determination is made that a portion of the grid is of insufficient quality to proceed with subsequent

processing, then that portion of the grid could be independently excluded from the remainder of the model creation 20 process. It should be noted that, in accordance with the present invention, histogram generation 80 could be performed at any point in the model creation 20 process.

Histogram generation 80 is accomplished in substantially the same manner as histogram generation 40, described above in relation to FIG. 4 and image qualification 18. The primary differences between histogram generation 80 and histogram generation 40 are that all, as opposed to a fraction of, available image data is processed during histogram generation 80 and that slope table values utilized during histogram generation 80 are the values generated during slope table generation 78 and not during slope table generation 38.

An important component to model creation 20 is indicated by block 82 in FIG. 15, namely wire-frame generation 82. Wire-frame generation 82 is the process of thinning to a special set of thin lines, illustratively referred to as wire-frame lines, the features, specifically, the fingerprint ridge line features, included within the monochrome image produced in accordance with preprocessing 76. FIG. 27 is a block diagram providing a detailed illustration of the procedural components of wire-frame generation 82 in accordance with an embodiment of the present invention.



One of the components of wire-frame generation  
82, as is indicated by block 122 in FIG. 27, is the  
location of pixels within the monochrome image that  
are the approximate center of a plurality of edges, in  
5 the current case, the approximate center of  
fingerprint ridge lines. Once the center pixels have  
been located, a thinned version of the monochrome  
image is created by thinning the ridge lines to the  
center pixels, so as to create a set of wire-frame  
10 lines. An effective method to locate pixels that are  
the approximate center of ridge lines and, at the same  
time, to thin the monochrome image to a set of wire-  
frame lines is as follows (of course, other methods  
could be used as well):

15

Equation 14

Set test pixel value 255.

Set replace pixel value to 254.

Repeat until no pixels are replaced

20 COMMENT process the image in the horizontal  
For y coordinate values of zero to number of  
lines do.

For x coordinate values of zero to number of  
pixels per lines do.

25 If pixel at image coordinates x and y is  
test pixel value

If pixel at image coordinates x+1 and  
y is 255

30 Set pixel at image coordinates  
x+1 and y to replace pixel value.

For x coordinate values of number of pixels  
per lines down to zero do.

If pixel at image coordinates x and y is  
test pixel value

35 If pixel at image coordinates x-1 and  
y is 255

```

                                Set pixel at image coordinates x-
1  1 and y to replace pixel value.
    COMMENT  process the image in the vertical
    For x coordinate values of zero to number of
5  pixels per lines do.
        For y coordinate values of zero to number of
lines do.
            If pixel at image coordinates x and y is
test pixel value
10         If pixel at image coordinates x and
y+1 is 255
                Set pixel at image coordinates x
and y+1 to replace pixel value.
            For y coordinate values of number of lines
15  down to zero do.
                If pixel at image coordinates x and y is
test pixel value
                    If pixel at image coordinates x and
20         y-1 is 255
                            Set pixel at image coordinates x
and y-1 to replace pixel value.
                    Decrement test pixel value by one.
                    Decrement replace pixel value by one

25         At this point, the center pixels will have the
lowest values. The process described below locates
these pixels.

Clear wire-frame image.
30  COMMENT  process the image in the horizontal
For y coordinate values of zero to number of lines
do.
    For x coordinate values of zero to number of
pixels per lines do.
35         Set test pixel to value in image at x and y
            If test pixel is not zero
                While pixel at image at x+1 and y is less
than test pixel
                    Set test pixel to value in image at
40         x+1 and y
                            Increment x by one.
                Set pixel in wire-frame image at x-1 and
y to 255.
            If pixel at x and y in image equals test pixel
```

Set pixel in wire-frame image at x-1 and y to 255.

Image 134 in FIG. 28 is an illustration of a monochrome image after a first removal of pixels from image ridge lines. Image 136 in FIG. 29 is an illustration of a monochrome image with a comprehensive representation of pixel removal passes made during the thinning of the monochrome image to center image line pixels. Image 138 in FIG. 30 is an illustration of FIG. 29 further including an overlay of a thinned monochrome image having raw wire-frame lines. Finally, image 140 in FIG. 31 is an illustration of a thinned monochrome image with raw wire-frame lines.

The block 122 (FIG. 27) thinning process produces a thinned version of the monochrome image that includes wire-frame lines that may be, in some places, more than one pixel thick. In addition, the thinned image as a whole may contain pixels that do not belong to any line. Accordingly, as is indicated by block 124 in FIG. 27, another component of wire-frame generation 82 is the removal of excess pixels 124. In accordance with one embodiment, component 124 proceeds as follows: the thinned version of the monochrome image is scanned until a non-zero valued pixel is located. Then, the surrounding eight pixels are utilized to form an index into a table. The entry in the table contains flags that define the potential operations to be performed, namely:

1. Remove center pixel.
2. Remove center pixel and set a new pixel (M).
3. Set a new pixel (N).

Below are the indexes into the table:

5

Equation 15

5 | 6 | 7 [where the index value is equal to  
---|---|--- the binary sum of pixel locations  
4 | P | 0 that are present and is represented  
10 ---|---|--- as a hexadecimal value (i.e.; pixel  
3 | 2 | 1 location 4 if present =  $2^{4th}$  which  
equals decimal value 16); and where  
Count equals the number of pixels  
present in a 3x3 array surrounding  
15 the center "P" pixel location.]

index value 0x00: Remove Point - Count = 0  
index value 0x00:  
20 index value 0x00: R R R R  
index value 0x00:  
  
index value 0x05: Remove Point - Count = 2  
index value 0x14: \* \*  
25 index value 0x50: R\* \*R \*R R\*  
index value 0x41: \* \*  
  
index value 0x07: Remove Point - Count = 3  
index value 0x1C: \*\* \*\*

index value 0x70:	R*	*R	*R	R*
index value 0xC1:			**	**

index value 0x0D:	Remove Point - Count = 3			
5 index value 0x34:	**	*		*
index value 0xD0:	R*	*R	*R	R*
index value 0x43:		*	**	*

index value 0x0E:	Remove Point - Count = 3			
10 index value 0x38:	***	*		*
index value 0xE0:	R	*R	R	R*
index value 0x83:		*	***	*

index value 0x0F:	Remove Point - Count = 4			
15 index value 0x3C:	***	**		*
index value 0xF0:	R*	*R	*R	R*
index value 0xC3:		*	***	**

index value 0x16:	Remove Point - Count = 3			
20 index value 0x58:	**	*		*
index value 0x61:	*R	*R	R*	R*
index value 0x85:		*	**	*

index value 0x1E:	Remove Point - Count = 4			
25 index value 0x78:	***	*		**
index value 0xE1:	*R	*R	R*	R*
index value 0x87:		**	***	*

index value 0x36:	Remove Point - Count = 4			
-------------------	--------------------------	--	--	--

index value 0xD8:	**	*	*	**
index value 0x63:	*R	*R	R*	
index value 0x8D:	*	**	**	

```

5  index value 0x3D:          Remove Point - Count = 5
   index value 0xF4:          **      *      *      ***
   index value 0xD3:          *R*    *R    *R*    R*
   index value 0x4F:          *      ***    **    *

```

```

10  index value 0x3E:      Remove Point - Count = 5
    index value 0xF8:      ***      *          *          ***
    index value 0xE3:      *R      *R          R*          R*
    index value 0x8F:      *          ***      ***          *

```

```

15  index value 0x3F:      Remove Point - Count = 6
    index value 0xFC:      ***      **      *      ***
    index value 0xF3:      *R*      *R      *R*      R*
    index value 0xCF:      *      ***      ***      **

```

20	index value 0xBF:	Remove Point - Count = 7			
	index value 0xFE:	***	***	* *	***
	index value 0xFB:	*R*	*R	*R*	R*
	index value 0xEF:	* *	***	***	***

25 \*\*\*\*\*

```

index value 0x0A:      Move Point - Count = 2
index value 0x28:      *M*      *      *
index value 0xA0:      X      MX      X      XM

```

index value 0x82:                   \*           \*M\*           \*

\*\*\*\*\*

5

index value 0x29:           New Point - Count = 3

index value 0xA4:           \*           \*           \*   \*N\*

index value 0x92:           NX\*           X           \*XN       X

10 index value 0x4A:           \*           \*N\*           \*       \*

index value 0x2B:           New Point - Count = 4

index value 0xAC:           \*N\*       \*\*           \*       \* \*

index value 0xB2:           X\*       NX           \*X           XN

15 index value 0xCA:           \*           \* \*           \*N\*           \*\*

index value 0x6A:           New Point - Count = 4

index value 0xA9:           \*N\*       \*           \*\*       \* \*

index value 0xA6:           X       NX\*           X           \*XN

20 index value 0x9A:           \*\*       \* \*           \*N\*           \*

index value 0xAB:           New Point - Count = 5

index value 0xAE:           \* \*       \*\*\*       \* \*       \*N\*

index value 0xBA:           NX\*           X           \*XN       X

25 index value 0xEA:           \* \*       \*N\*           \* \*       \*\*\*

Image 142 in FIG. 32 is an illustration of a thinned version of a monochrome image after excess pixels have been removed. Image 144 in FIG. 33 is an

illustration demonstrating the relationship between a thinned version of a monochrome without excess pixels and a corresponding monochrome image (monochrome image ridge lines in white).

5           In accordance with an embodiment of the present invention, after the thinned version of the monochrome image has been created and excess pixels have been removed from the wire-frame lines, as is illustrated by block 126 in FIG. 27, end-point and center-point  
10   tables are constructed. To create these tables, the wire-frame lines are scanned and all end-points (those pixels on the wire-frame lines that touch only one other pixel) are catalogued in the end-point table. Image 146 in FIG. 34 is an illustration of a thinned  
15   monochrome image (with excess pixels removed) that includes a representation of data from an end-point table (white dots represent end-points). As the wire-frame lines are scanned, the center-points (those pixels that touch more than two other pixels) are  
20   catalogued in the center-point table. Image 148 in FIG. 35 is an illustration of a thinned monochrome image that includes a representation of data from a center-point table (white dots represent center-points).

25           The points within end-point and center-point tables are used in subsequent processing. In one embodiment, the points are utilized to identify unique data elements, such as spikes, mouse bites and anti-ridges. These data elements can be identified and



catalogued through data describing the precise location of end-points or center-points, and slope values associated with lines attached to the points. The orientation of these data elements are unique to an individual system user and can be utilized to authenticate or match one set of image data to one or more other sets of image data.

After excess pixels have been removed from the wire-frame lines contained in the thinned monochrome image, the next step in wire-frame generation 82, in accordance with block 128 in FIG. 27, is to create a refined set of wire-frame lines by pruning excess branches. As can be seen in image 142 in FIG. 32, the wire-frame lines within the thinned monochrome image include many small branches protruding from the main lines. The removal of a selection of these branches leaves a refined set of wire-frame lines that are relatively smooth for subsequent minutiae and vector segment extraction.

In accordance with one embodiment, the block 128 branch removal process relies upon data taken from end-point and slope tables, both generated previously in the model creation 20 process. Each entry in the end-point table is used to locate a line segment that includes an end-point. The segment is traced back from the end-point along the corresponding line segment for seven pixels or until a center-point is located. If the segment length is less than five pixels, it is unconditionally removed (the pixels are

cleared from the image). If the segment terminates on a center-point, the slope of the segment is compared to the slope of image elements in the same proximity. Slope data is derived from the slope table. If the  
5 difference between the two slopes is greater than 25 degrees, the segment is removed. Image 150 in FIG. 36 is an illustration of a refined set of wire-frame lines that result from the removal of excess wire-frame branches. Image 152 in FIG. 37 is an  
10 illustration demonstrating the relationship between the refined set of wire-frame lines and a corresponding monochrome image (image ridge lines are in white).

After the refined set of wire-frame lines have  
15 been created, in accordance with one embodiment, excess pixels are once again removed from the image. In one embodiment, excess pixels are located and removed in the same manner as described above in relation to Equation 15. In one embodiment, the end-  
20 point table and center-point table are recomputed either before, but illustratively after excess pixels have once again been removed.

As is demonstrated by block 130 in FIG. 27, another procedural component of wire-frame generation  
25 82 is the fixing of end points. As can be seen in image 150 in FIG. 36, segments at the end of a line within the refined set of wire-frame lines may curl or may demonstrate a slope angle that is inconsistent with slope table entries in the same proximity.

In accordance with one embodiment and with block 130, in order to correct these deficiencies, each entry in the end-point table is utilized to assist in the creation of a further refined set of wire-frame lines. Accordingly, each entry in the end-point table is used to trace a corresponding line segment back seven pixels or until a center-point is encountered. If a center-point is encountered, the segment is restored. If no center-point is encountered, the line is removed from the wire-frame image. After the line is removed, the slope table entry for the line segment termination point is retrieved from the slope table. This slope value is utilized to create a new line segment, using a line draw algorithm, from the termination point to the end of the monochrome image. Image 154 in FIG. 38 is an illustration demonstrating the relationship between a further refined set of wire-frame lines, including fixed end points, and a corresponding monochrome image (image ridge lines are in white).

In accordance with one embodiment, the end-point and center-point tables are recomputed after end-points have been fixed in accordance with block 130 and the creation of a further refined set of wire-frame lines.

As is demonstrated by block 132 in FIG. 27, another procedural component of wire-frame generation is the joining of end-points. Fingerprint ridge data elements may be broken due to paper cuts,

blisters, burns, skin wrinkles, wet/dry conditions, or due to other image scanning problems, such as those caused by environmental influences in the image reader 12 environment. In accordance with end-point joining 5 132, an attempt is made to join end-points in a manner that bridges certain ridge gaps.

In accordance with one embodiment of end-point joining 132, each entry in the end-point table is compared to all other entries in the end-point table. 10 If any two points are within six pixels of each other and the slope of the corresponding lines are within 25 degrees of each other, the segments are joined. Image 156 in FIG. 39 is an illustration demonstrating the relationship between a further refined set of wire- 15 frame lines, including fixed and joined end-points, and a corresponding monochrome image (image ridge lines are in white). In accordance with one embodiment, the end-point and center-point tables are recomputed after end-points have been joined. After 20 the end-points have been joined within the further refined set of wire-frame lines, a complete wire-frame image, based on a corresponding monochrome image, in accordance with wire-frame generation 82, will have been completed.

25 After a monochrome image has been transformed into a completed wire-frame image, in accordance with an embodiment of the present invention, the next component of model creation 20, in accordance with block 84 in FIG. 15, is to analyze the completed wire-

frame image in order to locate fingerprint bifurcations and rods to be catalogued and included within an image model, along with other data elements. In accordance with one embodiment, relative to portion  
5 12 image resolution and with reference to FIG. 40, general data elements related to a bifurcation are as follows:

Equation 16

- 10     • Leg segments 162, 164 and 168. These segments are of equal length and each has at least one originating point at center-point 158. In accordance with one embodiment, each segment is set to 17 pixels.
- 15     • The coordinates of center-point 158. This point is used to define a bifurcation. The upper left corner of the image is assumed to have coordinates of 0,0. Positive x coordinates are right and positive y coordinates are down.
- 20     • First separation angle 160. This is the angle between leg segments 162 and 164, which is used to define a bifurcation. In accordance with one embodiment, first separation angle 160, by definition, cannot exceed 120 degrees.
- 25     • Direction angle 166. This angle is the direction of a bifurcation and is used to define a bifurcation. In accordance with one embodiment, direction angle 166 can have values between 0 and 359.
- 30     • It should be noted that the angle between leg segments 162 and 168 is the largest angle of all the angles between leg segments.
- 35     • A count of the number of 20 (illustratively 20) pixel segments tracing from point 158 along the wire-frame line connected to leg segment 162 is used to define data points associated with a bifurcation. It is assumed that this is the first leg segment array.

- A list (of length count) of the x and y coordinates of the 20 (illustratively 20) pixel segment end-points is constructed in order to catalogue data points within a first leg segment array. Leg segment array data points can also be called vector segment data points and, in accordance with one embodiment, and in accordance with the present invention, can be utilized to compare one image model to another. Bifurcations are used as one origin to catalogue vector segment data points.
- A count of the number of 20 (illustratively 20) pixel segments tracing from point 158 along the wire-frame line connected to leg segment 164 is constructed in order to catalogue data points within a second leg segment array.
- A list (of length count) of the x and y coordinates of the 20 (illustratively 20) pixel segment end-points is constructed in order to catalogue second leg segment array data points (vector segment data points).
- A count of the number of 20 (illustratively 20) pixel segment end-points tracing from point 158 along a wire-frame line connected to leg segment 168 is used to define data points associated with a bifurcation. It is assumed that this is the third leg segment array.
- A list (of length count) of the x and y coordinates of the 20 (illustratively 20) pixel segment end-points is constructed in order to catalogue third leg segment array data points (vector segment data points).
- In accordance with one embodiment, the maximum number of leg segments with each array of data points is 20 (illustratively 20).

It should be emphasized that the precise values, in particular values corresponding to pixel counts and segment counts, could be modified without departing from the current invention. Different reader portion 12 (FIG. 1) technologies may require

such modifications. The particular values provided in the present description in the context of illustrative embodiments, are to be considered illustrative values only.

- 5           In accordance with one embodiment of the present invention, location of a possible bifurcation starts with the center-point table created during wire frame generation 82. Each entry in the center-point table is considered a potential bifurcation. Starting with  
10 a center-point entry in the center-point table, each segment extending therefrom is traced. When a length of 17 pixels is reached, the corresponding x and y coordinates are placed in a list and a leg segment count is incremented. Tracing, however, will  
15 terminate upon one of the following conditions:
1. A count of 20 (illustratively 20) leg segments is reached.
  2. An end-point is detected (from EP table).
  3. A center-point from center-point table is  
20 detected.

When the line tracing has been completed, three angles can be computed for potential bifurcations:

1. The angle between leg segments 162 and 164.
2. The angle between leg segments 164 and 168.
- 25 3. The angle between leg segments 162 and 168.

These angles are sorted in ascending order. The smallest angle, between segments 162 and 164, is saved as the separation angle. Next, angle 166 is computed using point 167 as coordinates 0,0. After leg

segments have been identified and corresponding angles have been computed, a list of bifurcations will have been constructed. The bifurcations are illustratively defined through the center-point table.

5        A rod is considered a special case bifurcation. With reference to FIG. 41, wherein elements common to FIGS. 40 and 41 include identical labels, illustrative general data elements related to a rod, and assumptions based thereon, are as follows:

10

Equation 17

- The end-point 172 of rod 165. This point is the center point 158 of the special case bifurcation.
- 15    • The upper left corner of the image, again, is the coordinate 0,0. Positive values of x are to the right and positive values of y are down.
- Using as the direction the direction of the rod 165 segment extending from point 170 to end-point 172, the rod end is extended to points 162 and 164.
- 20    • Points 162 and 164 coincide.
- Direction angle 174 is the direction of the rod. In accordance with one embodiment, it is assumed that the direction angle can have values between 0 and 359.
- 25    • The angle between the segment extending between points 172 and 162, and the segment extending between point 172 and 164 (first separation angle 160) is set to zero.
- 30    • The segment extending from end-point 172 to points 162/164 is the same length as the segment extending from point 170 to end-point 172. In accordance with one embodiment, it is assumed that each segment is set to 17 (this value may vary) pixels.
- 35



- A count of the number of 20 (this value may vary) pixel segment end-points tracing from point 158 along rod 165 is used to define data points associated with a rod. It is assumed that this is the first leg segment array list.
- A list (of length count) of the x and y coordinates of the 20 (this value may vary) pixel segment end-points is constructed in order to catalogue the first leg segment array data points. These data points are vector segment data points and can be utilized to compare one image model to another.
- The two remaining segment array lists contain only one point, 162/164. This point is computed by extending the segment associated with the first segment array list by 17 (this value may vary) pixels.
- The maximum number of 20 (this value may vary) pixel segments in the first leg segment array is illustratively 20.

In accordance with one embodiment of the present invention, location of a possible rod starts with the end-point table created during wire frame generation

82. Each entry in the end-point table is considered a potential rod. Starting with an entry in the end-point table, the corresponding line segment is traced. When a length of 17 (this value may vary) pixels is reached, the corresponding x and y coordinates are place in a list and a leg segment count is incremented. Tracing terminates upon one of the following conditions:

1. A count of 20 (this value may vary) segments is reached.
2. An end-point is detected (from EP table).
3. A center-point from center-point table is

detected.

In accordance with an embodiment of the present invention, for rods to be included within an image model, they must meet certain qualifying standards.

5 Accordingly, after a vector segment has been traced, the segment extending from point 170 to end-point 172 is extended along the same angle to 162/164. If during extension, an image ridgeline is crossed, the corresponding rod is not saved and is not entered into

10 an image model. In addition, a line perpendicular to the segment extending from end-point 172 to point 162/164 is extended in both direction for a distance of an illustrative 20 (this value may vary) pixels. If neither of these 20 (this value may vary) pixel

15 lines intersect an image ridgeline, the rod is not saved. The distances during the perpendicular extension are then compared to see if end-point 172 is approximately the mid-point. If it is not, the rod is not saved. The output from this process is a list of

20 qualified rods, which are defined through the end-point table. Direction angle 174 is used to assist in defining rods and is computed using point 170 as coordinates 0,0.

In addition to being located, in order to be

25 included within an image model, rods and bifurcations must meet certain qualifications. As was previously mentioned, rods are qualified at the same time as they are located. Bifurcations, however, in accordance with block 86 in FIG. 15, in order to be included

within an image model, must fulfill several qualifications in addition to those imposed during the bifurcation location process. With reference to FIG. 40, in accordance with one embodiment, the following  
5 is a list of filter rules used to further qualify bifurcations for entry into an image model:

Equation 18

- 10       • As first separation angle 160 approaches 120 degrees, the risk of the separation angle being defined using the wrong legs increases. Accordingly, the first filter rule is that first separation angle 160 must be less than 115 degrees.
- 15       • At least two of the bifurcation legs must have three or more 20 (this value may vary) pixel segments.
- The slope of leg segments 162, 164 and 168 must be within 30 degrees of the slope table  
20       for the same area.

Image 176 in FIG. 42 is an illustration of a wire-frame image within which qualified bifurcations and rods have been circled. End-points and center-points are identified with white dots. Image 178 in  
25 FIG.43 is an illustration of a wire-frame image within which the same qualified bifurcations and rods have been circled. Within image 178, vector segment data points (the illustrative 20 pixel segments extending from a qualified rod or bifurcation) have been traced

and are shown in white. Vector segment data points approximately track wire-frame lines that connect to a qualified bifurcation and rod and can be used to compare one image model to another.

5           In accordance with block 88 in FIG. 15, the final step in the model creation 20 process is the building of an image model based on a completed wire-frame image and image elements derived therefrom. A completed image model consists of the following  
10 elements:

Equation 19

- A count of qualified bifurcations
- A count of qualified rods
- 15 • A bifurcation and rod list which consists of:

20           --The center point (center-point 158 for bifurcations or end-point 172 for rods, see FIGS. 40 and 41) identified with x and y coordinates.

          --The direction angle (angle 166 for bifurcations or angle 174 for rods)

          --The separation angle (angle 160 for bifurcations or a zero value for rods)

25           --Three leg segment arrays (vector segment arrays), which consist of:

- a) Count of 20 (this value may vary)  
pixel segments extending  
from a point within corresponding

rod/bifurcation.

b) List of x coordinate end-points  
corresponding to 20 (this value may  
vary) pixel segments.

5 c) List of y coordinate end-points  
corresponding to 20 (this value may  
vary) pixel segments.

• Data representations of line segments or  
vector segments not used by bifurcations or  
10 rods.

Bifurcations, within an image model, are defined  
by the intersection of ridge segments. Referring to  
FIG. 40, in accordance with one embodiment of the  
15 present invention, the information recorded in an  
image model for a bifurcation is as follows:

Equation 20

• The x and y coordinates of center point 158.  
20 • First separation angle 160.  
• Direction angle 166.  
• A list of the x and y coordinates that trace  
the vector/leg segments emanating from the  
center point 158. These points are equal  
25 distance (illustratively 20 pixels) apart.  
Tracing and collection of 20 (this value may  
vary) pixel vector/leg segments continues  
until:

--The trace terminates at the center of

a bifurcation.

--The end of the segment is reached.

--A maximum of forty 20 (this value may vary) pixel segments are recorded.

5

Rods are defined by the ending of a ridge segment. The end-point must be approximately half way between two ridge segments and if extended for a particular amount of pixels, illustratively 10 or 20 (or some other appropriate value), must not touch another ridge segment. In accordance with one embodiment, with reference to FIG. 41, the information recorded in an image model for a rod is as follows:

15 Equation 21

- The x and y coordinates of end-point 172.
- First separation angle 160 (by definition, this value is zero).
- Direction angle 174.
- A list of the x and y coordinates that trace the vector/leg segments emanating from point 172. These points are equal distance (illustratively 20 pixels) apart. Tracing continues until:

25

--Arrive at center of a bifurcation.

--The end of the wire-frame segment is reached.

--Maximum of forty 20 (this value may vary) pixel segments are recorded.

In accordance with an embodiment of the present invention, ridge segments not used by bifurcations or rods are recorded in an image model as follows:

5

Equation 22

- A list of x and y coordinates that trace the ridge segments emanating from end-points. These points are equal distance (illustratively 20 pixels) apart. Tracing continues until:
  - The trace terminates at the center of a bifurcation.
  - The end of the segment is reached.
  - A maximum of forty 20 (this value may vary) pixel segments are recorded.

10

15

In accordance with one embodiment, information within an image model can be stored in accordance with the following data storage format:

Equation 23

```
20  typedef struct tag_LEG
    {
        int  seperation_angle; // angle to next leg
        int  count;           // number of entries
                                // in row and col
25      int  row[ 40 ];       // y coordinate list
        int  col[ 40 ];       // x coordinate list
    } LEG, * LEG_PTR;

30  typedef struct tag_D_POINT // bifurcation or
                                rod information
    {
        int  row;             // bifurcation or
                                rod center y
```

```

                                coordinate
                                // bifurcation or
                                rod center y
                                coordinate
5      int  leg_orientation;    // orientation angle
      LEG  leg[ 3 ];           // leg trace info
      } D_POINT, * D_POINT_PTR;

10     typedef struct tag_SEG    // for extra segment
                                information
      {
      int count;                // number of entries
                                in row and col
      int  row[ 40 ];           // y coordinate list
15     int  col[ 40 ];           // x coordinate list
      } SEG, * SEG_PTR;

      typedef struct tag_PRINT    // model structure
20     {
      int  min_point_center_col;
      int  min_point_center_row;
      int  no_of_extra_segs;     // entries in
                                segment_list
25     int  no_of_points;        // # of bifurcations
                                in point_list
      int  no_of_islands;        // number of rods in
                                point_list
      D_POINT point_list[ 100 ]; // bifurcations and
30     SEG  segment_list[ 100 ]; // extra segment
                                list
      } PRINT, * PRINT_PTR;

      [DATA LIMITS CAN BE EXTENDED FOR DIFFERENT IMAGES]
35

```

It should again be emphasized that the precise values, in particular values corresponding to pixel counts and segments counts, could be modified without departing from the current invention. Different reader portion 12 (FIG. 1) technologies may require



such modifications. The values provided, whether explicitly indicated or not, are illustrative values only.

As is indicated by block 24 in FIG. 2, and in accordance with an embodiment of the present invention, a completed image model can be utilized as the basis for a model comparison. Model comparison 24 is a process for comparing one image model to another.

Model comparison can be accomplished by using a series of shift and rotate algorithms to adjust at least one image model and then counting the number of matching data elements. Data elements might include, but are not limited to bifurcation representations, rod representations, vector segments associated with bifurcation/rod representations, micro-minutia points and vector segments not incorporated into or associated with bifurcation/rod representations, and combinations thereof. When shifting and rotating causes the data element count to reach or approach a maximum value, the two models are at or approaching their maximum comparison point. Using the counts of the matching data elements at or near the maximum comparison point, a score, which represents the relationship or percentage of match, can be calculated.

The theory behind model comparison 24 is that as one model is rotated and shifted, the number of data element points that match will increase or decrease. If the number of points that match for each angle is

plotted, a bell shaped curve will result. The high point for the curve will represent the point at which the two models best compare.

In accordance with one embodiment of model comparison 24, the process starts by loosely comparing each bifurcation and rod in a model (model A) to all bifurcations and rods in another model (model B). The loose comparison enables a non-matching pair to be discovered without a significant investment of processing time. A more detailed comparison could illustratively be substituted for the loose comparison. In one embodiment, requirements utilized during the loose comparison are defined as:

15

Equation 24

- The center points must be within 90 (this value may vary) pixels in the x direction.
- The center points must be within 120 (this value may vary) pixels in the y direction.
- The difference between separation angles is within plus or minus 8 degrees.
- The difference between direction angles is within plus or minus 40 degrees.

25

In accordance with one embodiment, a possible match table is generated based on the loose comparison. The possible match table is indexed by the bifurcation or rod index into model A. Each entry in the possible match table consists of:

30

Equation 25

- A count of possible matches
- A list of the bifurcation or rod indexes in model B. This list defines all those points in model B that loosely match to the point in model A.

5           The general comparison process is best described by a simple coding example. Specifically, in accordance with one embodiment, the coding is defined as follows:

Equation 26

15           Generate possible match table.  
            Set maximum match count to zero.  
            Set rotate angle to zero.  
            Clear master x and y shift counts.  
TOP OF LOOP  
            If rotate angle is not zero  
                Rotate model B by rotate angle. This is a  
20       standard trig. function.  
                Shift process on model B (this is described below).  
                Count the bifurcations, rods and segments that match between model A and model B.  
25           

- The center points (both x and y) must be within 10 (this value may vary) pixels.
- The leg segment points (both x and y) must be within 10 (this value may vary) pixels.
- 30       • The difference for separation angle is within plus or minus 6 (this value may vary) degrees.
- The difference for direction angle is within plus or minus 10 (this value may vary) degrees.

  
35           If match count is less than maximum match count minus two  
            Exit the loop.  
40           If match count is greater than maximum match count

Set maximum match count to maximum count.  
Save rotate angle.  
Save x and y shift counts. This is an  
output of the above shift process.  
5 Increment rotate angle by one.  
If rotate angle is less than 30  
Goto TOP OF LOOP

10 The above loop is repeated for angles between -1  
and -30.

Copy working possible match table to possible  
match table. This will be used in the enrollment  
process.  
15 Using the saved variables rotate angle and x and  
y shift counts, shift and rotate the entire model B.  
Count the bifurcations, rods and segments that  
match between model A and model B.

- 20
- The center points (both x and y) must be within 10 (this value may vary) pixels.
  - The leg segment points (both x and y) must be within 10 (this value may vary) pixels.
  - The difference for separation angle is within plus or minus 6 (this value may vary) degrees.
  - The difference for direction angle is within plus or minus 10 (this value may vary) degrees.
- 25
- 30

#### SHIFT PROCESS DESCRIPTION

Set max test x to 90 (this value may vary) pix.  
Set max text y to 120 (this value may vary) pix.  
35 Clear master x and y shift counts.  
Make a working copy of the possible match table.  
TOP OF LOOP 1  
Clear saved points count.  
Clear delta x and delta y count.  
40 Set model A index to zero.  
TOP OF LOOP 2  
Set possible index to zero.  
TOP OF LOOP 3

Extract model B index from possible match table  
at model A index and possible index.

Compute the distance between the bifurcation or  
rod in model A and model B.

```
5      If the distance is less than max test x and max
      test y
          Increment saved points count.
          Add distance in x direction to delta x
count.
10     Add distance in y direction to delta y
count.
      Else
          Remove this point from the working copy of
the possible match table.
15     Increment possible index by one.
          If possible index is less than count value in
possible match tables at model A index.
          Goto TOP OF LOOP 3
          Increment model A index by one.
20     If model A index is less than the bifurcation
and rod count in model A
          Goto TOP OF LOOP 2

          If saved points count is zero
25     Exit the routine and return a value of zero
(no compare).
          Add delta x count divided by saved points count
to master x count.
          Add delta y count divided by saved points count
30 to master y count.
          Adjust all x and y coordinates in model B using
master x and y counts.
          If max test x is greater than 20 (this value may
vary) pixels
35     Multiply max test x by 0.75.
          Multiply max test y by 0.75.
          Goto TOP OF LOOP 1
          Exit the routine and return the value of saved
points count. (Those labeled and other specifically
40 noted values may be application-dependent.)

//      END CODE EXAMPLE
```

The result of the final shift and rotate process is several counts:

Equation 27

- 5     • The number of bifurcations that match.
- The number of rods that match.
- The number of segments that match.
- The number of segments that don't match.

10     For the discussion below, the following definitions are used:

Equation 28

- 15     • Total points: the sum of the number of bifurcations that match and the number of rods that match.
- Segments per leg: total segments matched divided by number of legs compared.
- 20     • Percent of points: total points (multiplied by 100) divided by the minimum of total bifurcations and rods in model A or model B.
- Raw percentage: the number of segments that match (multiplied by 100) divided by the sum of the segments that match and the segments that
- 25     don't match.

Using the above counts, a percentage of match can be calculated (below is illustrative example based one sample reader device...values may change

30     depending on the particular reader technology).

Equation 29

- If the number of segments that match is zero, the percentage of match is zero.
- 35    • If segments per leg is less than four, the percentage of match is zero.
- If total points is less than three, the percentage of match is zero.
- If total points is three or four, the percentage
- 40    of match is  $\frac{1}{4}$  of the percent of points.

- If total points is five and segments per leg is greater than four, the percentage of match is raw percentage multiplied by percent of points divided by 800.
- 5    • If total points is six through ten and
  - Segments per leg is four, the percentage of match is raw percentage multiplied by percent of points divided by 700.
  - 10    • Segments per leg is five through seven, the percentage of match is raw percentage multiplied by percent of points divided by 500.
  - 15    • Segments per leg is greater than eight, the percentage of match is raw percentage multiplied by percent of points divided by 300.
  - 20    • If total points is greater than 10, the percentage of match is raw percentage multiplied by percent of points divided by 100.

Alternatively, using the above counts, a relationship of match can be calculated.

#### 25    Alternate Equation 29

- If the number of total points is equal to zero then the relationship is equal to zero.
- If the rotation angle to align the images is more than the maximum allowed then the relationship is equal to zero. This value is tunable to work with different image sizes and aspect ratios.
- The relationship between two images can be defined as the relationship between scoring elements. These elements can include but are not limited to:
  - The number of bifurcation representations that match
  - The number of bifurcation representations that do not match
  - The number of rods that match
  - The number of rods that do not match

- The number of segment representations that match
- The number of segment representations that do not match
- 5     • The number of segment representations per leg
- A series of calculations are then done to determine the scoring element values, which includes:
  - 10     • To determine the scoring element for the number of bifurcations that match, we first use the number of bifurcations that match to decide the weighting factor to use in the calculation. The larger the number of
  - 15     bifurcations that match, the more you can weight the final score.
  - To determine the scoring element for the number of bifurcations that do not match, we first use the number of bifurcations that
  - 20     match to decide the weighting factor to use in the calculation. The larger the number of bifurcations that match, the less the weighting factor for the bifurcations that do not match.
  - To determine the scoring element for the number of rods that match, we first use the
  - 25     number of bifurcations that match to decide the weighting factor to use in the calculation. The number of rods that match are then used to further obtain the
  - 30     weighting factor for this element. The larger the number of rods that match and the number of bifurcations that match, the more you can weight the final score.
  - To determine the scoring element for the
  - 35     number of rods that do not match, we first use the number of bifurcations that match to decide the weighting factor to use in the calculation. The number of rods that match are then used to further obtain the
  - 40     weighting factor for this element. The larger the number of rods that match and the number of bifurcations that match, the less



the weighting factor for the rods that do not match.

- 5       • To determine the scoring element for the number of segments that match, the total segments that match are multiplied by a weighting factor and then divided by the total segments that are within the fingerprint model's overlap area.
- 10       • To determine the scoring element for the number of segments that do not match, the lets that do not match are multiplied by a weighting factor and divided by the number of legs that match.
- 15       • To determine the scoring element for the segments per leg, we first use the number of bifurcations that match to decide the weighting factor to use in the calculation. The number of rods that match are then used to further obtain the weighting factor for this element.
- 20       • These calculations are tunable to accommodate different image sizes and aspect ratios. These values are then added together to form a probability of relationship between the images. This value is then adjusted by how much of the two images actually overlap. The smaller the overlap area, the greater the correction to the probability of relationship value.
- 25
- 30

35       In accordance with one embodiment of the present invention, the level of similarity required, within an image identification based security system, before two image models are declared matching is adjustable. Similarity levels can be tuned based on the nature of the environment being secured. A strictly tuned system would provide maximum security by requiring a high match relationship or percentage, but may be more prone to accidentally rejecting a matching pair of

image models. Conversely, a loosely tuned system would require a lower match relationship or percentage and, accordingly, would provide a lower level of security. A loosely tuned system, however, would be  
5 more prone to mistaken match determinations and less prone to match rejections.

FIG. 44 is a block diagram illustrating a set of procedural components associated with a one-to-one image comparison process, in accordance with an  
10 embodiment of the present invention. Block 180 indicates a first illustrative step in the process, specifically, deriving a first image data set based on a first image and a second image data set based on the second image. The first and second image data sets  
15 include a plurality of data elements, which are illustratively, but not necessarily, associated with fingerprint images. The two data sets are model representations of the first and second images and are illustratively created as described above in relation  
20 to other Figures incorporated into the description of the present invention.

Block 182 indicates an optional performance of a loose comparison process. Illustratively, the first and second data element sets include a plurality of  
25 data elements types. Performance of the loose comparison, as described above, economizes the comparison process by eliminating those data elements in one of the two sets that do not fit within a predetermined qualifying range of deviation from a

data element of a same type in the other of the two sets.

Block 184 indicates a comparison of data elements from the first image data set with data elements from the second image data sets. Illustratively, as described above, data elements include defining characteristics that are numeric or mathematical in nature and facilitate comparison of data elements. For example, in accordance with one embodiment, during the comparison process, a qualifying range of deviation is selected or predetermined. The qualifying range of deviation represents a tolerated differential between a defining characteristic of at least one data element, of the first type, from the first image data set, and a corresponding at least one defining characteristic, of at least one data element, of the first type, from the second image data set. In accordance with one embodiment, multiple defining characteristics, each with a qualifying range of deviation, can be used to define a single data element type. In accordance with one embodiment, a count is generated of data elements from the first and second image data sets wherein the amount of deviation between the defining characteristics (or characteristic) is within the qualifying range of deviation. In essence, this count is a count of data elements in the first image data set that approximately match data elements in the second image data set.

Block 186 indicates an examination of the count of matching data elements to evaluate whether the count is a maximum value. If only one comparison has been performed, the maximum value will not have yet  
5 been found. In situations where the maximum value has not been obtained, as is indicated by block 188, one of the first and second data image sets, and its incorporated data elements, is re-positioned (e.g., rotated, shifted, or both). Then, the process returns  
10 to block 184, where a new comparison is made and a new count is generated.

The compare, count, re-position steps are illustratively repeated to produce a plurality of additional counts of the data elements in the first  
15 image data set that approximately match data elements in the second image data set. When, as described above, the count approaches a maximum value, the process proceeds.

Block 190 indicates comparison of the count value  
20 with a predetermined target value. In accordance with one embodiment, the predetermined target value represents a selected level of similarity required for the first and second images to be considered matching. The target value can be adjusted based on a desired  
25 level and comprehensiveness of an associated security application. As is indicated by block 192, if the count is greater than the predetermined target value, a positive match is indicated. As is indicated by block 194, if the count is less than the predetermined

target value, a negative match is indicated. In accordance with one embodiment, the count comparison could be performed on a relationship or percentage basis and relationships or percentages could be  
5 compared rather than counts.

As is indicated by block 26 in FIG. 2, and in accordance with an illustrative embodiment of the present invention, database search 26 could be performed in place of or in combination with model  
10 comparison 24. Database search 26 involves a quick and efficient determination as to which, if any, of potentially thousands (or more, i.e., millions) of image models included within a database exhibit a desired level of similarity, as compared to a  
15 supplied, i.e., a target image model.

In accordance with an embodiment of the present invention, in order to quickly identify a fingerprint from a database containing thousands (or millions or more) of prints, a set of database keys is defined.  
20 Due to many factors (finger too dry, finger too wet, position of the finger when placed on the scanner, distortions due to pressure, etc.), keys are general (approximate), rather than specific in nature. In accordance with the embodiment, these general keys  
25 form the basic foundation for high-speed general indexing.

In accordance with one embodiment, a set of keys is generated using some of the characteristics associated with bifurcation and rod image model

elements (defined above in relation to FIGS. 40 and 41). The information used in key generation for a bifurcation, with reference to FIG. 40, consists of the following characteristics:

5

Equation 30

- The coordinates of center point 158. The upper left corner of the image is assumed to have coordinates of 0,0. Positive x coordinates are right and positive y coordinates are down.
- A first separation angle between leg segments 162 and 164 (separation angle 160).
- A second separation angle between segments 164 and 168.
- The direction of the bifurcation (direction angle 166).

10

15

A rod is considered to be a special case of a bifurcation with the following assumptions made with reference to FIG. 41:

20

Equation 31

- The end point of the rod (end-point 172) becomes the center point of the bifurcation (center-point 158).
- Using as the direction the direction of the segment extending from point 170 to end-point 158/172, the rod end is extended to points 162/164.
- Points 162 and 164 coincide.
- The angle between the segments extending from point 158/172 to points 162 and 164 (first separation angle, previously referred to as separation angle 160) is zero.
- The angle between the segments extending from point 158/172 to points 164 and 170 (second separation angle, previously referred to as

25

30

35

direction angle 174) becomes the direction angle.

The information used in key generation for a rod is:

5

Equation 32

- The coordinates of center-point/endpoint 158/172.
- The first separation angle (separation angle 160) Using the above assumption, this angle is zero.
- The second separation angle (direction angle 174).

15       As print models are stored in the database, two tables are updated. The first table, KEY\_1, is a two dimensional array. The first index is the first separation angle the second index is the second separation angle. It should be noted that the first separation angle cannot exceed 120 degrees, and, in accordance with one embodiment, could be limited to 115 degrees. In addition, second separation angle cannot exceed 180 degrees. The direction angle can be any value between zero and 359. Therefore the array size of KEY\_1 is 116 (0 to 115) by 180 (0 to 179). The second table, KEY\_2, contains the key information. KEY\_2 is a single dimension array that is open-ended.

Each entry in KEY\_1 contains two elements, a count and an index into the KEY\_2 table. The element count defines the number of bifurcations or rods that have identical separation and direction angles. The index element defines the starting point for the keys contained in table KEY\_2. An entry in the KEY\_2 table consist of the following elements:

Equation 33

- The x coordinate (X\_CENTER) of the bifurcation center or rod end-point. The upper left corner of the image is assumed to have coordinates of 0,0.
- The y coordinate (Y\_CENTER) of the bifurcation center or rod end-point. The upper left corner of the image is assumed to have coordinates of 0,0.
- The index to the bifurcation or rod in the model.
- The direction angle.
- The model identification number. As model records are stored in the database, they are assigned unique numbers. These numbers start at a predetermined value, usually 10,000,000, and increment, by one, with each record added.
- The finger identification number. Each finger is assigned a numerical value starting with zero. The left pinkie is assigned zero, the left ring assigned one, the last assigned, right pinkie, is nine (left to right).
- Control flags. This element contains information about the finger model:
  - Is the record marked as deleted?

In accordance with an embodiment of the present invention, updating of the tables, KEY\_1 and KEY\_2, is best described by the following coding example:

Equation 34

```
Set model index to zero. // loop through all
                           bifurcations and
                           rods in the model

TOP OF LOOP 1
  Extract the direction angle (DA) from the model.
  Extract the first separation angle (SA1) from
  the model.
```



Extract the second separation angle(SA2) from  
the model.

Build the new entry for the KEY\_2 table.

```
5          • The x coordinate. Extracted from the model
           • The y coordinate. Extracted from the model
           • The direction angle.
10         • The index. Set to model index.
           • The model identification number. Passed
           into this routine.
           • The finger identification number. Passed
           into this routine.
15         • Control flags. Set to zero.

           Increment the count field in table KEY_1[ SA1][
           SA2 ] by one.

20 // Increment all remaining key 2 index fields in
   the KEY_1 table.
   // At this point the table KEY_1 can be thought of
   as a single dimension array with 41,760 (116
   times 360) entries.

25       Set update index to the product of SA1 times
           SA2.
TOP OF LOOP 2
       Increment update index by one.
30       If update index is less than 41,760
           Increment KEY_1[update
           index].key_2_start_index.
           Increment update index.
           Go to TOP OF LOOP 2

35       // make room in the KEY_2 table by sliding all
           entries, starting at
           // KEY_1[ SA1 ][ SA2 ] .key_2_start_index, up one.

40       Set update index to the number of entries
           contained in the KEY_2 table minus one.
           Set stop index to the value stored in KEY_1[ SA1
           ][ SA2 ].key_2_start_index.
```

TOP OF LOOP 3

If update index is greater than or equal to stop  
index

5 Copy the entry at update index to update  
index plus one.

Decrement update index by one.

Go to TOP OF LOOP 3

Store the new key, generated above, in the KEY\_2  
table at stop index.

10 Increment the number of entries contained in the  
KEY\_2 table by one.

// END CODE EXAMPLE

15

Tables KEY\_1 and KEY\_2 provide a means of  
locating all bifurcations and rods that have identical  
angle characteristics. Table KEY\_1 provides a count  
and a starting index. Table KEY\_2 provides the key  
20 data. Also, it should be noted that the data stored  
in table KEY\_2 is grouped such that all bifurcations  
and rods that have identical angle characteristics are  
contiguous.

After the tables have been constructed, the next  
25 step is to identify matching model images. Those  
prints that have a large number of bifurcations and  
rods that loosely match to an entry in the database  
are most likely to compare with a high score. Using  
the above tables and some filter rules, a possible  
30 match table is created. Each entry in the possible  
match table contains the following information:

Equation 35

- A count of the number of bifurcations and rods  
35 that loosely match.

- The distance, in both the x and y, between the two center points (stored as an ordered pair).

Where loosely matched is defined to be:

- 5
- The center points must be within 90 (this and other specifically named values may vary) pixels in the x direction.
  - The center points must be within 120 (may vary) pixels in the y direction.
  - The angle difference for first separation angle is within plus or minus 8 degrees.
  - The angle difference for second separation angle is within plus or minus 8 (may vary) degrees.
  - The direction angle is within plus or minus 20 (this value may vary) degrees.
- 10
- 15

This table is indexed using the model identification number and finger identification number. In accordance with one embodiment, the table is created as follows:

20

Equation 36

Clear the possible match table.  
Set model index to zero.  
TOP OF LOOP 1  
Extract a model element.

25

// PROCESSING FOR BIFURCATIONS

30

If the element is a bifurcation  
Extract first separation angle from model.  
Extract second separation angle from model.  
Extract direction angle from model.  
Extract center point coordinate from model.  
Set start index 1 to first separation angle minus the deviation (8 degrees).  
If start index 1 is less than one  
Set start index 1 to 1.  
Set stop index 1 to first separation angle plus the deviation (8 degrees).

35

40

```

        If stop index 1 is greater than 116
            Set stop index 1 to 116.
        Set start index 2 to second separation
angle minus the deviation (8 degrees).
5         If start index 2 is less than one
            Set start index 2 to 1.
        Set stop index 2 to second separation angle
plus the deviation (8 degrees).
        Set index 1 to start index 1.
10      TOP OF LOOP 2
        Set index 2 to start index 2.
      TOP OF LOOP 3
        Set loop count to the value of the count
        element in table KEY1[ index 1 ][ index 2 ]
15         If loop count is not zero
            Set key 2 index to index value in
            table KEY1[ index 1 ][ index 2 ]

20      TOP OF LOOP 4
        If the "loosely matched rules",
        defined above, are met
            Use model identification and
            finger model numbers to form an index
25             into the possible match table.
            Increment the match count and store
            the distance difference.
            Increment key 2 index by one.
            Decrement loop count
30             If loop count is greater than zero
                Goto TOP OF LOOP 4
            Increment index 2
            If index 2 is greater than stop index 2
                Goto TOP OF LOOP 3
35             Increment index 1
            If index 1 is greater than stop index 1
                Goto TOP OF LOOP 2

      //      PROCESSING FOR RODS
40
        If the element is a rod
            Extract direction angle from model.
            Extract center point coordinate from model.
```

```

        Set start index 1 to direction minus the
deviation (20 degrees).
        If start index 1 is less than zero
            Set start index 1 to zero.
5         Set stop index 1 to direction plus the
deviation (20 degrees).
        If stop index 1 is greater than 359
            Set stop index 1 to 359.

10        Set index 1 to start index 1.
        TOP OF LOOP 5
            Set loop count to the value of the count
            element in table KEY1[ 0 ][ index 2 ]
            If loop count is not zero
15             Set key 2 index to index value in
table KEY1[ 0 ][ index 2 ]
        TOP OF LOOP 6
            If the "loosely matched rules",
defined above, are met
20             Use model identification and
            finger model numbers to form an index
            into the possible match table.
            Increment the match count and store
            the distance difference.
25             Increment key 2 index by one.
            Decrement loop count
            If loop count is greater than zero
                Goto TOP OF LOOP 6

30             Increment index 1
            If index 1 is greater than stop index 1
                Goto TOP OF LOOP 5
            Increment model index by 1.
            If model index is less than total model elements
35             Goto TOP OF LOOP 1

        //          END OF CODE EXAMPLE

40        At this point, the possible match table contains
a list of all models in the database that are
candidates for comparison. The count field contains a

```

count of the bifurcations and rods that loosely match. The distance list contains an ordered list, count value entries, of the distances from the center point of model to those of entries in the database. Some of these entries are invalid. The filter rule below attempts to remove some invalid values. To remove invalid entries the distance list is first sorted, using the x distance, in ascending order (see example below). This list is then scanned looking for the longest sequence of numbers whose distance is less than 40. The start and end index of this list is then used to sort the y component of the ordered pairs. The list is then scanned looking for the longest sequence of numbers whose distance is less than 40. The start and end index of this list provides a new count to replace the old count.

Equation 37

x	-61	-34	-32	-23	-12	-11	-7	-3	-2	5	11	14	14	19	24	26	28
y	86	69	-99	31	6	-59	-119	116	114	-125	7	-16	32	-12	-76	125	-87
					*	*	*	*	*	*	*	*	*	*	*	*	*
y	86	69	-99	31	-125	-119	-59	-16	6	7	32	114	116	-12	-76	125	-87
									*	*	*						

In the above example, the original count is 17. Following the first sort and index location, the start index is 4 and the end index is 12 (represented by asterisk). The second sort and index location yields a count of 3.

When all match counts have been adjusted, the table is sorted, in descending order, by count. Those entries at the top of the list (the highest count values) represent those models (from the database) that should be compared to the supplied live scan.

Qualification parameters can be adjusted at several levels to accommodate the reader 12 characteristics and overall security level as it relates to false matches versus false rejections. As an example, the match table  
5 distance parameter could be expanded to consider entries whose distance is greater than 60 versus 40, which would have the net effect of lowering the security level thereby reducing false rejections at the expense of increasing false accepts.

10 FIG. 45 is a block diagram illustrating a set of procedural components associated with a one-to-many, or database search, image comparison process, in accordance with an embodiment of the present invention. Block 196 indicates a first illustrative  
15 step in the process, specifically, deriving a first image data set based on a first image and a plurality of other image data sets based on a plurality of other images. The first and other image data sets include a plurality of data elements, which are illustratively,  
20 but not necessarily, associated with fingerprint images. Different data element types associated with fingerprint images are described above in relation to one-to-one comparisons, as well as in other locations within the present description.

25 The image data sets derived for the first and other images are illustratively model representations of corresponding first and other images. The image data sets are illustratively generated as described

above in relation to other Figures incorporated into the description of the present invention.

The next step, indicated by block 198, is the creation of a directory that progressively lists, based on at least one measured characteristic (e.g., a particular angle, length, etc.), a substantial number of a particular type of data elements (e.g., one of bifurcation representations, rod representations, vectors associated and not associated therewith, microminutia points, etc.) that appear in the plurality of other image data sets. Each data element in the directory is illustratively listed with an identifier that represents association with a particular image data set within which the data element appears.

Block 200 indicates the next step in the process, wherein an array is created that includes a two-entry cell for each of a range (or substantially all) of potential configurations for the same one type of data elements that are listed in the directory created in step 198.

Block 202 indicates a recording of process information within array cells. In accordance with one embodiment, in one entry of each two-entry cell is recorded a quantity value representing a number of consecutive data elements in the directory that demonstrate characteristics that are approximately similar to characteristics of the one of the range of potential configurations that corresponds to the data



element configuration associated with that two-entry cell. Illustratively, in the other entry of each two-entry cell is recorded an index value corresponding to an initial data element that begins the number of  
5 consecutive data elements listed in the directory. In other words, the cells are utilized to record locations within the progressive directory of data elements that potentially match the data element associated with a given cell location.

10       Block 204 indicates the next step, wherein there is an identification of a two-entry cell in the array that is associated with a data element configuration having characteristics approximately identical to a target data element, a data element taken from the  
15 first image data set.

Block 206 indicates the next step, wherein the target data element is compared to a group of consecutive data elements listed in the directory, as indicated by the two-entry cell associated with that  
20 target data element. As is indicated by block 208, this identification and comparison of target data elements to associated consecutive data elements in the directory is repeated for additional target data elements.

25       Block 210 indicates the next step. The step comprises calculating and noting a quantity of data elements in each of the plurality of other image data sets that approximately match data elements, illustratively target data elements, taken from the

first image data set. As target data elements are found to match data elements in the directory, the above-mentioned identifiers assist in knowing which image data set to which an increase in count should be made.

As is indicated by block 212, similar directories, arrays, and counts can be made for numerous data element types. Illustratively, steps 198 through 210 are performed utilizing a variety of data element types and a single running count is kept for each of the other image data sets.

Block 214 indicates the next process step. The step comprises selecting from the plurality of other image data sets a predetermined number of image data sets that include the highest count, or the most data elements that approximately match target data elements taken from the first image data set.

Finally, block 216 indicates performing a more thorough comparison of the predetermined number of image data sets to the first image data set. The more thorough comparison process is illustratively utilized to distinguish between the image data sets, and consequently images, that should or should not be considered matching. In accordance with one embodiment, the one-to-one comparison process described in relation to FIG. 44 is utilized as the more thorough comparison process.

FIG. 46 is a block diagram illustrating a set of procedural components associated with another one-to-

many, or database search, image comparison process, in accordance with another embodiment of the present invention. Block 218 indicates a first illustrative step in the process, specifically, deriving a first  
5 image data set based on a first image and a plurality of other image data sets based on a plurality of other images. The first and other image data sets include a plurality of data elements, which are illustratively, but not necessarily, associated with fingerprint  
10 images. Different data element types associated with fingerprint images are described above in relation to one-to-one comparisons, as well as in other locations within the present description.

The image data sets derived for the first and  
15 other images are illustratively model representations of corresponding first and other images. The image data sets are illustratively generated as described above in relation to other Figures incorporated into the description of the present invention.

20 Block 220 indicates a step in the process comprising the creation of a B-tree data file for each of a plurality of data element types (e.g., bifurcation representations, rod representations, vectors associated with or independent of vector/rod  
25 representations, microminutia points, etc.). It should be pointed out that a B-tree data file is a data storage structure that is well known in the fields of data storage and data analysis. Illustratively, each B-tree data file is associated

with a different data element type and includes substantially all of the data elements included in the other image data sets (not the first/target image data set). The data elements from the other image data sets are illustratively listed and categorized in the B-tree data files based on data normalization rules. Each data element listed in each B-tree data file is stored with an identifier that represents association with a particular image data set in which that data element appears. In accordance with one embodiment, each B-tree data file reflects normalization rules for a corresponding data element type, including variations of relative position and/or rotation. In accordance with another embodiment, each B-tree data file reflects substantially all potential relative associations between data elements stored in the data file and the plurality of data element types.

Block 222 indicates a comparing of at least one target data element (data element from first image data set) to data elements in B-tree data files having data elements of a same type as the target data element being compared. In other words, a target data element is taken from the first image data set and progressively compared through a corresponding (of the same data element type) B-tree. The purpose is to look for data elements in the B-tree data files that approximately match the target data element.

The process steps indicated by blocks 224, 226 and 228 are substantially and respectively similar to

blocks 210, 214 and 216 described in relation to FIG. 45. For example, as is indicated by block 224, as target data elements are found to match data elements stored in a B-tree data file, for each of the plurality of other image data sets, a count is generated of included data elements that approximately match a target data element.

Block 226 indicates the next process step. The step comprises selecting from the plurality of other image data sets a predetermined number of image data sets that include the highest count, or the most data elements that approximately match target data elements taken from the first image data set. Finally, block 228 indicates performing a more thorough comparison of the predetermined number of image data sets to the first image data set. The more thorough comparison process is illustratively utilized to distinguish between the image data sets, and consequently images, that should or should not be considered matching. In accordance with one embodiment, the one-to-one comparison process described in relation to FIG. 44 is utilized as the more thorough comparison process.

Although the present invention has been described with reference to illustrative embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.